



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/727,360	12/03/2003	Akira Misawa	5259-000037	5505
27572 7590 12/23/2008 HARNESS, DICKEY & PIERCE, P.L.C. P.O. BOX 828 BLOOMFIELD HILLS, MI 48303				
EXAMINER SMITH, JOSHUA Y				
ART UNIT 2419		PAPER NUMBER		
MAIL DATE 12/23/2008		DELIVERY MODE PAPER		

**Please find below and/or attached an Office communication concerning this application or proceeding.**

The time period for reply, if any, is set in the attached communication.

### Office Action Summary

**Application No.**

10/727,360

**Applicant(s)**

MISAWA ET AL.

**Examiner**

JOSHUA SMITH

**Art Unit**

2419

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --  
**Period for Reply**

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

**Status**

- 1) ☒ Responsive to communication(s) filed on 25 August 2008.
- 2a) ☒ This action is **FINAL**. 2b) ☐ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

**Disposition of Claims**

- 4) ☒ Claim(s) 1-10, 13-15, 17-33 and 40-74 is/are pending in the application.
- 4a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.
- 5) ☐ Claim(s) \_\_\_\_\_ is/are allowed.
- 6) ☒ Claim(s) 1-10, 13-15, 17, 19-33 and 40-74 is/are rejected.
- 7) ☒ Claim(s) 18 is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

**Application Papers**

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on \_\_\_\_\_ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.  
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

**Priority under 35 U.S.C. § 119**

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some \* c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
  2. ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.
  3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

\* See the attached detailed Office action for a list of the certified copies not received.

**Attachment(s)**

- 1) ☐ Notice of References Cited (PTO-892)
- 2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)
- 3) ☒ Information Disclosure Statement(s) (PTO/SB/08)  
Paper No(s)/Mail Date \_\_\_\_\_
- 4) ☐ Interview Summary (PTO-413)  
Paper No(s)/Mail Date \_\_\_\_\_
- 5) ☐ Notice of Informal Patent Application
- 6) ☐ Other: \_\_\_\_\_

### DETAILED ACTION

The amendment filed 08/25/2008 has been entered.

- **Claims 1-10, 13-15, 17-33 and 40-74 are pending.**
- **Claims 11, 12, 16 and 34-39 are cancelled.**
- **Claim 18 is objected to.**
- **Claims 1-10, 13-15, 17, 19-33 and 40-74 stand rejected.**

#### *Claim Objections*

**Claim 18** is objected to under 37 CFR 1.75(c) as being in improper form because a multiple dependent claim should refer to other claims in the alternative only and a multiple dependent claim cannot depend from any other multiple dependent claim. See MPEP § 608.01(n). Accordingly, the claims have not been further treated on the merits.

**Claims 23, 25 and 33** are objected to under 37 CFR 1.75(c) as being in improper form because a multiple dependent claim cannot depend from any other multiple dependent claim. See MPEP § 608.01(n). Accordingly, the claims have not been further treated on the merits.

Applicant is advised that should **claim 26** be found allowable, **claim 33** will be objected to under 37 CFR 1.75 as being a substantial duplicate thereof. When two claims in an application are duplicates or else are so close in content that they both

cover the same thing, despite a slight difference in wording, it is proper after allowing one claim to object to the other as being a substantial duplicate of the allowed claim. See MPEP § 706.03(k).

Applicant is advised that should **claim 48** be found allowable, **claim 57** will be objected to under 37 CFR 1.75 as being a substantial duplicate thereof. When two claims in an application are duplicates or else are so close in content that they both cover the same thing, despite a slight difference in wording, it is proper after allowing one claim to object to the other as being a substantial duplicate of the allowed claim. See MPEP § 706.03(k).

Applicant is advised that should **claim 40** be found allowable, **claim 47** will be objected to under 37 CFR 1.75 as being a substantial duplicate thereof. When two claims in an application are duplicates or else are so close in content that they both cover the same thing, despite a slight difference in wording, it is proper after allowing one claim to object to the other as being a substantial duplicate of the allowed claim. See MPEP § 706.03(k).

Applicant is advised that should **claim 58** be found allowable, **claim 69** will be objected to under 37 CFR 1.75 as being a substantial duplicate thereof. When two claims in an application are duplicates or else are so close in content that they both cover the same thing, despite a slight difference in wording, it is proper after allowing

one claim to object to the other as being a substantial duplicate of the allowed claim.  
See MPEP § 706.03(k).

Applicant is advised that should **claim 70** be found allowable, **claim 74** will be objected to under 37 CFR 1.75 as being a substantial duplicate thereof. When two claims in an application are duplicates or else are so close in content that they both cover the same thing, despite a slight difference in wording, it is proper after allowing one claim to object to the other as being a substantial duplicate of the allowed claim.  
See MPEP § 706.03(k).

#### ***Claim Rejections - 35 USC § 112***

1. The following is a quotation of the second paragraph of 35 U.S.C. 112:

The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the applicant regards as his invention.

**Claims 9, 10, 21, 25, 32, 56, 57** are rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention.

**Claim 9** states "**a section** for performing the alternate converting operation which is disposed in the OVPN terminating device **according to Claim 2** commonly" (emphasis added by examiner). This is indefinite since it is unclear if Claim 9 is a dependent claim and includes all limitations of Claim 2, or if Claim 9 is an independent claim and includes only a portion of the limitations of Claim 2. Also, if Claim 9 is an

independent claim, it is unclear which of the multiple sections of Claim 2 is being claimed in Claim 9.

**In addition, Claim 9** states “according to Claim 2 **commonly**”, which is indefinite since only Claim 2 is stated, but “commonly” suggests multiple claims are stated.

**Claim 10** is rejected through dependence from Claim 9.

**Claim 21** states “A base point device which is disposed between the **OVPN system according to Claim 9** and the user’s device which is contained in the OVPN system or in a OVPN terminating device or between the **OVPN terminating device according to Claim 9** and the user’s device which is contained in the OVPN system or in a OVPN terminating device” (emphasis added by examiner). This is indefinite since the preamble makes is unclear whether all limitations of Claim 99 are included in Claim 21. In addition, the preamble doesn’t relate well to the body of the claim.

**Claim 25** depends from cancelled Claim 11.

**Claim 32** states “according to Claim 2 **commonly**”, which is indefinite since only Claim 2 is stated, but “commonly” suggests multiple claims are stated.

**Claim 56** states “according to Claim 49 **commonly**”, which is indefinite since only Claim 49 is stated, but “commonly” suggests multiple claims are stated.

**Claim 57** is rejected through dependence from Claim 56.

***Claim Rejections - 35 USC § 103***

1. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

2. The factual inquiries set forth in *Graham v. John Deere Co.*, 383 U.S. 1, 148 USPQ 459 (1966), that are applied for establishing a background for determining obviousness under 35 U.S.C. 103(a) are summarized as follows:

1. Determining the scope and contents of the prior art.
2. Ascertaining the differences between the prior art and the claims at issue.
3. Resolving the level of ordinary skill in the pertinent art.
4. Considering objective evidence present in the application indicating obviousness or nonobviousness.

**Claims 1-4, 7, 8, 9, 10 and 32** are rejected under 35 U.S.C. 103(a) as being unpatentable over EP 1229692 in view of Morinaga et al. (Patent No.: US 6,785,263 B1) and Oguchi et al. (Pub. No.: US 2002/0067725 A1), hereafter referred to as the '692 reference, Morinaga, and Oguchi, respectively.

**In regards to Claims 1 and 2**, the '692 reference teaches in paragraph [0005], page 2, lines 40-43, 48-49 and 52-55, an optical transport network is intended to be a multi-service network that supports a wide variety of layers including SDH STM-N, SONET, ATM, IP, as well as other formats, to provide a universal transport medium for high bandwidth services, where client signals are mapped into the payload area of a frame structure called an optical transport unit (OUT), and where the payload to be

carried from the client, i.e. the client signal, which may be ATM, SDH, STM-N, or IP, is mapped into an optical payload unit (OPU), and, in paragraph [0019], page 5, lines 50-55, and in Fig. 1, page 18, a node N1 (Fig. 1), a node SNA (Fig. 1), a node SNB (Fig. 1), and a node N1 (Fig. 1) at the edges a conventional SDH network (optical network, and a plurality of converting sections, which are disposed so as to correspond to plural different first signal formats, for converting a first signal format and a second signal format alternatively under conditions in which the first signal format is used by a user's device and a second signal format which is used in the network are different from each other, and a terminating device for containing the user's device).

The '692 reference fails to teach a registering section from the user's device for a first signal format type which is used in the user's device, a retrieving section for a first signal format type which corresponds to information in a user's device according to a calling connection request from a user's device by referring to the information which is registered by the registering section, and a selecting section for selecting a first signal format which is used by the user's device according to a result in the retrieving section when data is transported from the user's device, user's device joins an virtual private network, IP address of a user's device and a VPNID, and a notifying section for notifying contents of a registration to other VPN terminating device which controls that same VPNID as the user's device.

Morinaga teaches in column 5, line 60 though column 6, line 6, and in column 7, lines 45-59, and in FIG. 2, Sheet 2 of 9, a H.323 protocol portion (item 33, FIG. 2), a CODEC (item 34, FIG. 2), and a call control portion (item 31, FIG. 2), that operate



where a transmission format to be used in accordance with each user information of a calling side is registered as a circuit, and a CODEC to be used in accordance with each user information of the calling side is registered as the CODEC, and if the user information of a calling side is accompanied by ON flag in the target parameter setting table, the reference table of the user information of the calling side and communication method is looked up, so that the transmission format to be used as the communication method is decided (a registering section from the user's device for a first signal format type which is used in the user's device, a retrieving section for a first signal format type which corresponds to information in a user's device according to a calling connection request from a user's device by referring to the information which is registered by the registering section, and a selecting section for selecting a first signal format which is used by the user's device according to a result in the retrieving section when data is transported from the user's device). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Morinaga since Morinaga teaches a system that involves storing user information and transmission parameters, allowing the system of the '692 reference to be able to adjust routing parameters that best serve a user's preferences or QoS requirements.

Oguchi teaches in paragraph [0065], [0067], [0083], [0085], and [0143], virtual routers having the same VPN-ID exchange routing information though a level-2 tunnel established between edge routers, which can involves a host having an IP address, and then generate routing tables for that VPN-ID (user's device joins an virtual private

network, IP address of a user's device and a VPNID, and a notifying section for notifying contents of a registration to other VPN terminating device which controls that same VPNID as the user's device). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Oguchi since Oguchi provides a method of establishing a virtual network and distributing the necessary information to establish and maintain such a virtual network, allowing the optical network of the '692 reference to provide optical VPN services to customers and provide the privacy, robustness, and cost effectiveness of virtual private networks.

**In regards to Claims 3 and 4**, the '692 reference teaches in paragraph [0005], page 2, lines 40-43, 48-49 and 52-55, an optical transport network is intended to be a multi-service network that supports a wide variety of layers including SDH STM-N, SONET, ATM, IP, as well as other formats, to provide a universal transport medium for high bandwidth services, where client signals are mapped into the payload area of a frame structure called an optical transport unit (OUT), and where the payload to be carried fro the client, i.e. the client signal, which may be ATM, SDH, STM-N, or IP, is mapped into an optical payload unit (OPU), and, in paragraph [0019], page 5, lines 50-55, and in Fig. 1, page 18, a node N1 (Fig. 1), a node SNA (Fig. 1), a node SNB (Fig. 1), and a node N1 (Fig. 1) at the edges a conventional SDH network (optical network, and a plurality of converting sections, which are disposed so as to correspond to plural different first signal formats, for converting a first signal format and a second signal

format alternatively under conditions in which the first signal format is used by a user's device and a second signal format which is used in the network are different from each other, and a terminating device for containing the user's device).

The '692 reference fails to teach a registering section from the user's device for a first signal format type which is used in the user's device, a retrieving section for a first signal format type which corresponds to information in a user's device according to a calling connection request from a user's device by referring to the information which is registered by the registering section, and a selecting section for selecting a first signal format which is used by the user's device according to a result in the retrieving section when data is transported from the user's device, a receiving and selecting section which receives a first signal format type information which is used in a device which receives a calling connection request from another VPN terminating device so as to respond to a notice from the notifying section and selects a first signal format type which is used in a user's device according to a format type information, user's device joins an virtual private network, IP address of a user's device and a VPNID, and a notifying section for notifying contents of a registration to other VPN terminating device which controls that same VPNID as the user's device.

Morinaga teaches in column 5, line 60 though column 6, line 6, and in column 7, lines 45-59, and in FIG. 2, Sheet 2 of 9, a H.323 protocol portion (item 33, FIG. 2), a CODEC (item 34, FIG. 2), and a call control portion (item 31, FIG. 2), that operate where a transmission format to be used in accordance with each user information of a calling side is registered as a circuit, and a CODEC to be used in accordance with each

user information of the calling side is registered as the CODEC, and if the user information of a calling side is accompanied by ON flag in the target parameter setting table, the reference table of the user information of the calling side and communication method is looked up, so that the transmission format to be used as the communication method is decided (a registering section from the user's device for a first signal format type which is used in the user's device, a retrieving section for a first signal format type which corresponds to information in a user's device according to a calling connection request from a user's device by referring to the information which is registered by the registering section, and a selecting section for selecting a first signal format which is used by the user's device according to a result in the retrieving section when data is transported from the user's device).

Morinaga also teaches in column 5, lines 42-47 and 53-56, and in FIG. 2, Sheet 2 of 9, the central office line board (item 40, FIG. 2) is controlled by the central office line driver (item 39, FIG. 2), and the signal that the central office line driver transmits to or receives from the circuit exchange PBX1 via the central line office is processed by the switched circuit control portion (item 35, FIG. 2), and a signal that each of the LAN circuit drivers (item 37, FIG. 2) transmits or receives from the local area network via a LAN circuit board (item 38, FIG. 2) is processed by the LAN control portion (item 36, FIG. 2) (a receiving and selecting section which receives a first signal format type information which is used in a device which receives a calling connection request from another VPN terminating device so as to respond to a notice from the notifying section and selects a first signal format type which is used in a user's device according to a

format type information). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Morinaga since Morinaga teaches a system that involves storing user information and transmission parameters, allowing the system of the '692 reference to be able to adjust routing parameters that best serve a user's preferences or QoS requirements.

Oguchi teaches in paragraph [0065], [0067], [0083], [0085], and [0143], virtual routers having the same VPN-ID exchange routing information through a level-2 tunnel established between edge routers, which can involve a host having an IP address, and then generate routing tables for that VPN-ID (user's device joins a virtual private network, IP address of a user's device and a VPNID, and a notifying section for notifying contents of a registration to other VPN terminating device which controls that same VPNID as the user's device). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Oguchi since Oguchi provides a method of establishing a virtual network and distributing the necessary information to establish and maintain such a virtual network, allowing the optical network of the '692 reference to provide optical VPN services to customers and provide the privacy, robustness, and cost effectiveness of virtual private networks.

**In regards to Claim 7**, as discussed in the rejection of Claim 2, the '692 reference in view of Morinaga and Oguchi teaches an OVPN terminating device and a

registering section that registers information for a user's own device which corresponds to a first signal format which is used in a user's device with an IP address of a user's device and a VPNID.

The '692 reference fails to teach a port identifier.

Oguchi further teaches in paragraphs [0045] and [0202], a virtual router correspondence table that includes port numbers (a port identifier). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Oguchi since Oguchi provides a method of establishing a virtual network and distributing the necessary information to establish and maintain such a virtual network, allowing the optical network of the '692 reference to provide optical VPN services to customers and provide the privacy, robustness, and cost effectiveness of virtual private networks.

**In regards to Claim 8**, as discussed in the rejection of Claim 2, the '692 reference in view of Morinaga and Oguchi teaches an OVPN terminating device and a converting section. The '692 reference further teaches an operation in a user's own device. The '692 reference further teaches in paragraph [0008], page 3, lines 17-19, optical transport network data entities are clients of SDH or SONET, implicitly teaching the components of these entities are already treated as clients in the optical network and can be implemented in client equipment (an operation in a user's own device).

**In regards to Claim 9**, as discussed in the rejections of Claim 2, the '692 reference in view of Morinaga and Oguchi teaches an OVPN terminating device and a plurality of converting sections which are disposed to correspond to plural different signal formats, for converting a first signal format and a second signal format alternately under conditions in which a first signal format which is used by a user's device which joins an OVPN and a second signal which is used in an OVPN are different from each other.

The '692 reference fails to teach a section for performing an alternate converting operation.

Morinaga teaches in column 5, line 60 through column 6, line 6, and in column 7, lines 45-59, and in FIG. 2, Sheet 2 of 9, a H.323 protocol portion (item 33, FIG. 2), a CODEC (item 34, FIG. 2), and a call control portion (item 31, FIG. 2), that operate where a transmission format to be used in accordance with each user information of a calling side is registered as a circuit, and a CODEC to be used in accordance with each user information of the calling side is registered as the CODEC, and if the user information of a calling side is accompanied by ON flag in the target parameter setting table, the reference table of the user information of the calling side and communication method is looked up, so that the transmission format to be used as the communication method is decided (a section for performing an alternate converting operation). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Morinaga since Morinaga teaches a system that involves storing user information and transmission

parameters, allowing the system of the '692 reference to be able to adjust routing parameters that best serve a user's preferences or QoS requirements.

**In regards to Claim 10**, the '692 reference teaches in paragraph [0005], page 2, lines 40-43, 48-49 and 52-55, an optical transport network is intended to be a multi-service network that supports a wide variety of layers including SDH STM-N, SONET, ATM, IP, as well as other formats, to provide a universal transport medium for high bandwidth services, where client signals are mapped into the payload area of a frame structure called an optical transport unit (OUT), and where the payload to be carried from the client, i.e. the client signal, which may be ATM, SDH, STM-N, or IP, is mapped into an optical payload unit (OPU), and, in paragraph [0019], page 5, lines 50-55, and in Fig. 1, page 18, a node N1 (Fig. 1), a node SNA (Fig. 1), a node SNB (Fig. 1), and a node N1 (Fig. 1) at the edges a conventional SDH network (optical network, and a plurality of converting sections, which are disposed so as to correspond to plural different first signal formats, for converting a first signal format and a second signal format alternatively under conditions in which the first signal format is used by a user's device and a second signal format which is used in the network are different from each other, and a terminating device for containing the user's device).

The '692 reference fails to teach a registering section from the user's device for a first signal format type which is used in the user's device, a retrieving section for a first signal format type which corresponds to information in a user's device according to a calling connection request from a user's device by referring to the information which is



registered by the registering section, and a selecting section for selecting a first signal format which is used by the user's device according to a result in the retrieving section when data is transported from the user's device, user's device joins an virtual private network, IP address of a user's device and a VPNID, and a notifying section for notifying contents of a registration to other VPN terminating device which controls that same VPNID as the user's device, and a section for performing an alternate converting operation.

Morinaga teaches in column 5, line 60 through column 6, line 6, and in column 7, lines 45-59, and in FIG. 2, Sheet 2 of 9, a H.323 protocol portion (item 33, FIG. 2), a CODEC (item 34, FIG. 2), and a call control portion (item 31, FIG. 2), that operate where a transmission format to be used in accordance with each user information of a calling side is registered as a circuit, and a CODEC to be used in accordance with each user information of the calling side is registered as the CODEC, and if the user information of a calling side is accompanied by ON flag in the target parameter setting table, the reference table of the user information of the calling side and communication method is looked up, so that the transmission format to be used as the communication method is decided (a registering section from the user's device for a first signal format type which is used in the user's device, a retrieving section for a first signal format type which corresponds to information in a user's device according to a calling connection request from a user's device by referring to the information which is registered by the registering section, and a selecting section for selecting a first signal format which is

used by the user's device according to a result in the retrieving section when data is transported from the user's device).

Morinaga teaches in column 5, line 60 through column 6, line 6, and in column 7, lines 45-59, and in FIG. 2, Sheet 2 of 9, a H.323 protocol portion (item 33, FIG. 2), a CODEC (item 34, FIG. 2), and a call control portion (item 31, FIG. 2), that operate where a transmission format to be used in accordance with each user information of a calling side is registered as a circuit, and a CODEC to be used in accordance with each user information of the calling side is registered as the CODEC, and if the user information of a calling side is accompanied by ON flag in the target parameter setting table, the reference table of the user information of the calling side and communication method is looked up, so that the transmission format to be used as the communication method is decided (a section for performing an alternate converting operation). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Morinaga since Morinaga teaches a system that involves storing user information and transmission parameters, allowing the system of the '692 reference to be able to adjust routing parameters that best serve a user's preferences or QoS requirements.

Oguchi teaches in paragraph [0065], [0067], [0083], [0085], and [0143], virtual routers having the same VPN-ID exchange routing information though a level-2 tunnel established between edge routers, which can involves a host having an IP address, and then generate routing tables for that VPN-ID (user's device joins an virtual private network, IP address of a user's device and a VPNID, and a notifying section for notifying

contents of a registration to other VPN terminating device which controls that same VPNID as the user's device). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Oguchi since Oguchi provides a method of establishing a virtual network and distributing the necessary information to establish and maintain such a virtual network, allowing the optical network of the '692 reference to provide optical VPN services to customers and provide the privacy, robustness, and cost effectiveness of virtual private networks.

**In regards to Claim 32**, as discussed in the rejection of Claim 2, the '692 reference in view of Oguchi teaches an OVPN terminating device and a plurality of converting sections which are disposed to correspond to plural different signal formats, for converting a first signal format and a second signal format alternately under conditions in which a first signal format which is used by a user's device which joins an OVPN and a second signal which is used in an OVPN are different from each other.

The '692 reference fails to teach a section for performing an alternate converting operation.

Morinaga teaches in column 5, line 60 through column 6, line 6, and in column 7, lines 45-59, and in FIG. 2, Sheet 2 of 9, a H.323 protocol portion (item 33, FIG. 2), a CODEC (item 34, FIG. 2), and a call control portion (item 31, FIG. 2), that operate where a transmission format to be used in accordance with each user information of a calling side is registered as a circuit, and a CODEC to be used in accordance with each

user information of the calling side is registered as the CODEC, and if the user information of a calling side is accompanied by ON flag in the target parameter setting table, the reference table of the user information of the calling side and communication method is looked up, so that the transmission format to be used as the communication method is decided (a section for performing an alternate converting operation). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Morinaga since Morinaga teaches a system that involves storing user information and transmission parameters, allowing the system of the '692 reference to be able to adjust routing parameters that best serve a user's preferences or QoS requirements.

**Claims 5 and 6** are rejected under 35 U.S.C. 103(a) as being unpatentable over the '692 reference in view of Morinaga, Oguchi, and Zboril (Pub. No.: US 2003/0117945 A1), hereafter referred to as Zboril.

**In regards to Claims 5 and 6**, the '692 reference teaches in paragraph [0005], page 2, lines 40-43, 48-49 and 52-55, an optical transport network is intended to be a multi-service network that supports a wide variety of layers including SDH STM-N, SONET, ATM, IP, as well as other formats, to provide a universal transport medium for high bandwidth services, where client signals are mapped into the payload area of a frame structure called an optical transport unit (OUT), and where the payload to be carried from the client, i.e. the client signal, which may be ATM, SDH, STM-N, or IP, is mapped into an optical payload unit (OPU), and, in paragraph [0019], page 5, lines 50-

55, and in Fig. 1, page 18, a node N1 (Fig. 1), a node SNA (Fig. 1), a node SNB (Fig. 1), and a node N1 (Fig. 1) at the edges a conventional SDH network (optical network, and a plurality of converting sections, which are disposed so as to correspond to plural different first signal formats, for converting a first signal format and a second signal format alternatively under conditions in which the first signal format is used by a user's device and a second signal format which is used in the network are different from each other, a selecting section which selects for an alternate converting operation when a first signal format which is selected is different from a second signal format type, and a terminating device for containing the user's device).

The '692 reference fails to teach a registering section for registering a first signal format type which is sent from a user's device so as to be used in the user's device, and selecting a first signal format type which can be used in a user's device handled between other VPN terminating device and the user's own device commonly according to registered contents, a user's device joins an virtual private network, IP address of a user's device and a VPNID, and a notifying and selecting section for notifying registered contents to another VPN terminating device which controls a device, a retrieving section retrieves information of a vacancy of a section for an operation in a one device and another device, and selecting an operation not occupied for one device and another device according to retrieving results by a retrieving section.

Morinaga teaches in column 5, line 60 through column 6, line 6, and in column 7, lines 45-59, and in FIG. 2, Sheet 2 of 9, a H.323 protocol portion (item 33, FIG. 2), a CODEC (item 34, FIG. 2), and a call control portion (item 31, FIG. 2), that operate

where a transmission format to be used in accordance with each user information of a calling side is registered as a circuit, and a CODEC to be used in accordance with each user information of the calling side is registered as the CODEC, and if the user information of a calling side is accompanied by ON flag in the target parameter setting table, the reference table of the user information of the calling side and communication method is looked up, so that the transmission format to be used as the communication method is decided (a registering section for registering a first signal format type which is sent from a user's device so as to be used in the user's device, and selecting a first signal format type which can be used in a user's device handled between other VPN terminating device and the user's own device commonly according to registered contents). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Morinaga since Morinaga teaches a system that involves storing user information and transmission parameters, allowing the system of the '692 reference to be able to adjust routing parameters that best serve a user's preferences or QoS requirements.

Oguchi teaches in paragraph [0065], [0067], [0083], [0085], and [0143], virtual routers having the same VPN-ID exchange routing information through a level-2 tunnel established between edge routers, which can involve a host having an IP address, and then generate routing tables for that VPN-ID (user's device joins an virtual private network, IP address of a user's device and a VPNID, and a notifying and selecting section for notifying registered contents to another VPN terminating device which controls a device). It would have been obvious to one of ordinary skill in the art at the

time of the invention to combine the invention of the '692 reference with the invention of Oguchi since Oguchi provides a method of establishing a virtual network and distributing the necessary information to establish and maintain such a virtual network, allowing the optical network of the '692 reference to provide optical VPN services to customers and provide the privacy, robustness, and cost effectiveness of virtual private networks.

Zboril teaches in paragraphs [0130], [0156], and [0158], and in FIG. 1, Sheet 1 of 10, and in FIG. 3, Sheet 3 of 10, a continuous sequence of idle cells is sent on all inactive links that are indicated in TFU information, and idle cells are also inserted whenever no data cells are available on a data link (item 120, FIG. 3), and a link is brought into service by a multi-fiber transmitter (a retrieving section retrieves information of a vacancy of a section for an operation in a one device and another device, and selecting an operation not occupied for one device and another device according to retrieving results by a retrieving section). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Zboril since Zboril provides a method for each device in an optical network to exchange status information, providing the devices in the optical network of the '692 reference a method of information exchange that will allow thorough and rapid updates of network configuration changes and network failures.

**Claims 13, 22, 23 and 25** are rejected under 35 U.S.C. 103(a) as being unpatentable over the '692 reference in view of Newell, Jr. et al. (Patent No.: US

6,668,319 B1) and French et al. (Pub. No.: 2003/0041167 A1), hereafter referred to as Newell and French, respectively.

**In regards to Claim 13**, the '692 reference teaches in paragraph [0005], page 2, lines 40-43, 48-49 and 52-55, an optical transport network is intended to be a multi-service network that supports a wide variety of layers including SDH STM-N, SONET, ATM, IP, as well as other formats, to provide a universal transport medium for high bandwidth services, where client signals are mapped into the payload area of a frame structure called an optical transport unit (OUT), and where the payload to be carried from the client, i.e. the client signal, which may be ATM, SDH, STM-N, or IP, is mapped into an optical payload unit (OPU), and, in paragraph [0019], page 5, lines 50-55, and in Fig. 1, page 18, a node N1 (Fig. 1), a node SNA (Fig. 1), a node SNB (Fig. 1), and a node N1 (Fig. 1) at the edges a conventional SDH network (optical network, and a plurality of converting sections, which are disposed so as to correspond to plural different first signal formats, for converting a first signal format and a second signal format alternatively under conditions in which the first signal format is used by a user's device and a second signal format which is used in the network are different from each other, and a terminating device for containing the user's device, and performing alternate converting operations).

The '692 reference fails to teach a retrieving section for detecting whether or not there is a section for performing an operation, a notifying section to determine whether or not a format is used by another device and notify that the formats do not coincide each other for setting up a service to a user's device, a generating section for



generating an IP address and a VPNID to a user's device, and a registering section for registering an IP address and a VPNID generated by a generating section and information used by a user's device to which an IP address and a VPNIS are added.

Newell teaches in column 4, lines 11-27, devices exchange information concerning which protocol feature teaches does or does not support (a retrieving section for detecting whether or not there is a section for performing an operation). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Newell since Newell provides a method in which devices in a network can inform other devices of network capabilities, allowing devices to make appropriate decision when routing requests, allowing the system of the '692 reference to performing routing based on the capabilities of other devices.

Newell teaches in column 4, lines 11-27, devices exchange information concerning which protocol feature each does or does not support (a notifying section to determine whether or not a format is used by another device and notify that the formats do not coincide each other for setting up a service to a user's device). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Newell since Newell provides a method in which devices in a network can inform other devices of network capabilities, allowing devices to make appropriate decision when routing requests, allowing the system of the '692 reference to performing routing based on the capabilities of other devices.

French teaches in paragraphs [0227] and [0275], assigned VPN IDs are stored as updated information within network objects, and a VPN creator ensures unique VPN IDs are created such that duplicate addresses can exist within a VPN that has an assigned VPN ID, and a server generates an IP address on behalf of its client (a generating section for generating an IP address and a VPNID to a user's device, and a registering section for registering an IP address and a VPNID generated by a generating section and information used by a user's device to which an IP address and a VPNIS are added). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of French since French provides a system of maintaining and updating VPN IDs for IP addresses within virtual private networks, allowing the optical network of the '692 reference to provide optical VPN services to customers and provide the privacy, robustness, and cost effectiveness of virtual private networks.

**In regards to Claim 22**, as discussed in the rejection of Claim 13, the '692 reference in view of French teaches an OVPN terminating device and a converting section. The '692 reference further teaches an operation in a user's own device. The '692 reference further teaches in paragraph [0008], page 3, lines 17-19, optical transport network data entities are clients of SDH or SONET, implicitly teaching the components of these entities are already treated as clients in the optical network and can be implemented in client equipment (an operation in a user's own device).

**In regards to Claim 23**, as discussed in the rejection of Claim 58, the '692 reference in view of Miyabe and Oguchi teaches a user's device and an OVPN.

The '692 reference fails to teach a separating section for separating a user's device and a network, and a returning section for returning a test beam which is transmitted from a network.

Tosey teaches in column 7, lines 14-17 and 29-31, and in FIG. 2, Sheet 2 of 11, a network computing device (item 21, FIG. 2) that is part of a network of other network devices, and this network is separated from a WAN of users by a router (item 24, FIG. 2), and where the network computing device (item 21, FIG. 2) executes a link test to a peer network device, such as the router (item 24, FIG. 2), and determines if a peer network device has returned a response (a separating section for separating a user's device and a network, and a returning section for returning a test beam which is transmitted from a network). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Tosey since Tosey provides a method of testing connections of a network device to other network devices, including devices that connect it to another network and its users, and where the device being tested can respond to confirm connectivity, including connectivity to a network of users, allowing the system of the '692 reference to detect network failures and respond by developing paths to avoid them and reestablish connectivity.

**In regards to Claim 25**, the '692 reference teaches in paragraph [0005], page 2, lines 40-43, 48-49 and 52-55, an optical transport network is intended to be a multi-service network that supports a wide variety of layers including SDH STM-N, SONET, ATM, IP, as well as other formats, to provide a universal transport medium for high bandwidth services, where client signals are mapped into the payload area of a frame structure called an optical transport unit (OUT), and where the payload to be carried from the client, i.e. the client signal, which may be ATM, SDH, STM-N, or IP, is mapped into an optical payload unit (OPU), and, in paragraph [0019], page 5, lines 50-55, and in Fig. 1, page 18, a node N1 (Fig. 1), a node SNA (Fig. 1), a node SNB (Fig. 1), and a node N1 (Fig. 1) at the edges a conventional SDH network (optical network, and a plurality of converting sections, which are disposed so as to correspond to plural different first signal formats, for converting a first signal format and a second signal format alternatively under conditions in which the first signal format is used by a user's device and a second signal format which is used in the network are different from each other, and a terminating device for containing the user's device, and performing alternate converting operations).

The '692 reference fails to teach a retrieving section for detecting whether or not there is a section for performing an operation, a notifying section to determine whether or not a format is used by another device and notify that the formats do not coincide each other for setting up a service to a user's device, a generating section for generating an IP address and a VPNID to a user's device, and a registering section for

registering an IP address and a VPNID generated by a generating section and information used by a user's device to which an IP address and a VPNIS are added.

Newell teaches in column 4, lines 11-27, devices exchange information concerning which protocol feature teaches does or does not support (a retrieving section for detecting whether or not there is a section for performing an operation). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Newell since Newell provides a method in which devices in a network can inform other devices of network capabilities, allowing devices to make appropriate decision when routing requests, allowing the system of the '692 reference to performing routing based on the capabilities of other devices.

Newell teaches in column 4, lines 11-27, devices exchange information concerning which protocol feature each does or does not support (a notifying section to determine whether or not a format is used by another device and notify that the formats do not coincide each other for setting up a service to a user's device). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Newell since Newell provides a method in which devices in a network can inform other devices of network capabilities, allowing devices to make appropriate decision when routing requests, allowing the system of the '692 reference to performing routing based on the capabilities of other devices.

French teaches in paragraphs [0227] and [0275], assigned VPN IDs are stored as updated information within network objects, and a VPN creator ensures unique VPN IDs are created such that duplicate addresses can exist within a VPN that has an assigned VPN ID, and a server generates an IP address on behalf of its client (a generating section for generating an IP address and a VPNID to a user's device, and a registering section for registering an IP address and a VPNID generated by a generating section and information used by a user's device to which an IP address and a VPNIS are added). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of French since French provides a system of maintaining and updating VPN IDs for IP addresses within virtual private networks, allowing the optical network of the '692 reference to provide optical VPN services to customers and provide the privacy, robustness, and cost effectiveness of virtual private networks.

**Claims 14, 15, 19, 20, 24, 26, 27, 29, 33, 48 and 57** are rejected under 35 U.S.C. 103(a) as being unpatentable over the '692 reference in view of Newell, French, and Morinaga.

**In regards to Claim 14**, as discussed in the rejection of Claim 13, the '692 reference in view of Newell and French teaches a user's device having an IP address and a first signal format type information used by a user's device.

The '692 reference fails to teach a selecting section for selecting a first signal format which is used by the user who receives a calling connection request according to

a first signal format type information which is used by a user's device, included in a calling connection request, from which a calling connection request is transmitted when a calling connection request is received from a user's device, and a transmitting section for transmitting format type information which is selected by a sleeting section to a user who receives a calling connection request together with a calling connection request.

Morinaga teaches in column 5, line 60 though column 6, line 6, and in column 7, lines 45-59, and in column 12, lines 18-25, and in FIG. 2, Sheet 2 of 9, and in FIG. 5, Sheet 5 of 9, a H.323 protocol portion (item 33, FIG. 2), a CODEC (item 34, FIG. 2), and a call control portion (item 31, FIG. 2), that operate where a transmission format to be used in accordance with each user information of a calling side is registered as a circuit, and a CODEC to be used in accordance with each user information of the calling side is registered as the CODEC, and if the user information of a calling side is accompanied by ON flag in the target parameter setting table, the reference table of the user information of the calling side and communication method is looked up, so that the transmission format to be used as the communication method is decided, and a request of setup is propagated to opposite site of the intended connection (item #311, FIG. 5) based on selection of CODEC and format (a selecting section for selecting a first signal format which is used by the user who receives a calling connection request according to a first signal format type information which is used by a user's device, included in a calling connection request, from which a calling connection request is transmitted when a calling connection request is received from a user's device, and a transmitting section for transmitting format type information which is selected by a sleeting section to a user

who receives a calling connection request together with a calling connection request). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Morinaga since Morinaga teaches a system that involves storing user information and transmission parameters for use in efficient connection setup.

**In regards to Claim 15**, as discussed in the rejection of Claim 14, the '692 reference in view of Newell and French teaches a signal format and receiving a response to a calling connection request.

The '692 reference fails to teach a notifying section to determine whether or not a format is used by another device and notify that the formats do not coincide each other for setting up a service to a user's device.

Newell teaches in column 4, lines 11-27, devices exchange information concerning which protocol feature teaches does or does not support (a notifying section to determine whether or not a format is used by another device and notify that the formats do not coincide each other for setting up a service to a user's device). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Newell since Newell provides a method in which devices in a network can inform other devices of network capabilities, allowing devices to make appropriate decision when routing requests, allowing the system of the '692 reference to performing routing based on the capabilities of other devices.



**In regards to Claims 19 and 20**, the '692 reference teaches in paragraph [0005], page 2, lines 40-43, 48-49 and 52-55, an optical transport network is intended to be a multi-service network that supports a wide variety of layers including SDH STM-N, SONET, ATM, IP, as well as other formats, to provide a universal transport medium for high bandwidth services, where client signals are mapped into the payload area of a frame structure called an optical transport unit (OTU), and where the payload to be carried from the client, i.e. the client signal, which may be ATM, SDH, STM-N, or IP, is mapped into an optical payload unit (OPU), and, in paragraph [0019], page 5, lines 50-55, and in Fig. 1, page 18, a node N1 (Fig. 1), a node SNA (Fig. 1), a node SNB (Fig. 1), and a node N1 (Fig. 1) at the edges a conventional SDH network (optical network, and a plurality of converting sections, which are disposed so as to correspond to plural different first signal formats, for converting a first signal format and a second signal format alternatively under conditions in which the first signal format is used by a user's device and a second signal format which is used in the network are different from each other, and a terminating device for containing the user's device, and performing alternate converting operations).

The '692 reference fails to teach a retrieving section for detecting whether or not there is a section for performing an operation, a generating section for generating an IP address and a VPNID to a user's device, and a registering section for registering an IP address and a VPNID generated by a generating section and information used by a user's device to which an IP address and a VPNIS are added, a section for employing a

converting section for performing an operation of a first signal format and a second signal format which correspond to an IP address which is contained in a calling connection request which is transmitted from a communication flowing a calling connection request by referring to a registering section when a calling connection request arrives from a user's device.

Newell teaches in column 4, lines 11-27, devices exchange information concerning which protocol feature teaches does or does not support (a retrieving section for detecting whether or not there is a section for performing an operation). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Newell since Newell provides a method in which devices in a network can inform other devices of network capabilities, allowing devices to make appropriate decision when routing requests, allowing the system of the '692 reference to performing routing based on the capabilities of other devices.

French teaches in paragraphs [0227] and [0275], assigned VPN IDs are stored as updated information within network objects, and a VPN creator ensures unique VPN IDs are created such that duplicate addresses can exist within a VPN that has an assigned VPN ID, and a server generates an IP address on behalf of its client (a generating section for generating an IP address and a VPNID to a user's device, and a registering section for registering an IP address and a VPNID generated by a generating section and information used by a user's device to which an IP address and a VPNID are added). It would have been obvious to one of ordinary skill in the art at the

time of the invention to combine the invention of the '692 reference with the invention of French since French provides a system of maintaining and updating VPN IDs for IP addresses within virtual private networks, allowing the optical network of the '692 reference to provide optical VPN services to customers and provide the privacy, robustness, and cost effectiveness of virtual private networks.

Morinaga teaches in column 5, line 60 through column 6, line 6, and in column 7, lines 45-59, and in FIG. 2, Sheet 2 of 9, a H.323 protocol portion (item 33, FIG. 2), a CODEC (item 34, FIG. 2), and a call control portion (item 31, FIG. 2), that operate where a transmission format to be used in accordance with each user information of a calling side is registered as a circuit, and a CODEC to be used in accordance with each user information of the calling side is registered as the CODEC, and if the user information of a calling side is accompanied by ON flag in the target parameter setting table, the reference table of the user information of the calling side and communication method is looked up, so that the transmission format to be used as the communication method is decided (a section for employing a converting section for performing an operation of a first signal format and a second signal format which correspond to an IP address which is contained in a calling connection request which is transmitted from a communication flowing a calling connection request by referring to a registering section when a calling connection request arrives from a user's device). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Morinaga since Morinaga teaches a system that involves storing user information and transmission parameters, allowing the

system of the '692 reference to be able to adjust routing parameters that best serve a user's preferences or QoS requirements.

**In regards to Claim 24**, as discussed in the rejections of Claim 13, the '692 reference in view of French teaches an OVPN terminating device and a plurality of converting sections which are disposed to correspond to plural different signal formats, for converting a first signal format and a second signal format alternately under conditions in which a first signal format which is used by a user's device which joins an OVPN and a second signal which is used in an OVPN are different from each other.

The '692 reference fails to teach a section for performing an alternate converting operation.

Morinaga teaches in column 5, line 60 through column 6, line 6, and in column 7, lines 45-59, and in FIG. 2, Sheet 2 of 9, a H.323 protocol portion (item 33, FIG. 2), a CODEC (item 34, FIG. 2), and a call control portion (item 31, FIG. 2), that operate where a transmission format to be used in accordance with each user information of a calling side is registered as a circuit, and a CODEC to be used in accordance with each user information of the calling side is registered as the CODEC, and if the user information of a calling side is accompanied by ON flag in the target parameter setting table, the reference table of the user information of the calling side and communication method is looked up, so that the transmission format to be used as the communication method is decided (a section for performing an alternate converting operation). It would have been obvious to one of ordinary skill in the art at the time of the invention to

combine the invention of the '692 reference with the invention of Morinaga since Morinaga teaches a system that involves storing user information and transmission parameters, allowing the system of the '692 reference to be able to adjust routing parameters that best serve a user's preferences or QoS requirements.

**In regards to Claim 26**, as discussed in the rejection of Claim 13, the '692 reference teaches an OVPN system.

The '692 reference fails to teach a receiving and determining section for receiving a test signal which is transmitted via a data channel by using an identifier from a user's device and determining a first signal format type which belongs to a user's device.

Morinaga teaches in column 5, line 60 through column 6, line 6, and in column 7, lines 45-59, and in FIG. 2, Sheet 2 of 9, a H.323 protocol portion (item 33, FIG. 2), a CODEC (item 34, FIG. 2), and a call control portion (item 31, FIG. 2), that operate where a transmission format to be used in accordance with each user information of a calling side is registered as a circuit, and a CODEC to be used in accordance with each user information of the calling side is registered as the CODEC, and if the user information of a calling side is accompanied by ON flag in the target parameter setting table, the reference table of the user information of the calling side and communication method is looked up, so that the transmission format to be used as the communication method is decided, and, in column 9, lines 41-54, and in FIG. 3, Sheet 3 of 9, a gateway receives a calling signal and a target parameter setting a table is looked up as to judge

parameters (a receiving and determining section for receiving a test signal which is transmitted via a data channel by using an identifier from a user's device and determining a first signal format type which belongs to a user's device). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Morinaga since Morinaga teaches a system that involves storing user information and transmission parameters, allowing the system of the '692 reference to be able to adjust routing parameters that best serve a user's preferences or QoS requirements.

**In regards to Claim 27**, the '692 reference teaches in paragraph [0005], page 2, lines 40-43, 48-49 and 52-55, an optical transport network is intended to be a multi-service network that supports a wide variety of layers including SDH STM-N, SONET, ATM, IP, as well as other formats, to provide a universal transport medium for high bandwidth services, where client signals are mapped into the payload area of a frame structure called an optical transport unit (OUT), and where the payload to be carried from the client, i.e. the client signal, which may be ATM, SDH, STM-N, or IP, is mapped into an optical payload unit (OPU), and, in paragraph [0019], page 5, lines 50-55, and in Fig. 1, page 18, a node N1 (Fig. 1), a node SNA (Fig. 1), a node SNB (Fig. 1), and a node N1 (Fig. 1) at the edges a conventional SDH network (optical network, and a plurality of converting sections, which are disposed so as to correspond to plural different first signal formats, for converting a first signal format and a second signal format alternatively under conditions in which the first signal format is used by a user's device

and a second signal format which is used in the network are different from each other, and a terminating device for containing the user's device, and performing alternate converting operations).

The '692 reference fails to teach a retrieving section for detecting whether or not there is a section for performing an operation, a generating section for generating an IP address and a VPNID to a user's device, and a registering section for registering an IP address and a VPNID generated by a generating section and information used by a user's device to which an IP address and a VPNIS are added, a detection section for detecting whether or not a user's device is connected, and a receiving and determining section for receiving a test signal which is transmitted via a data channel by using an identifier from a user's device and determining a first signal format type which belongs to a user's device.

Newell teaches in column 4, lines 11-27, devices exchange information concerning which protocol feature teaches does or does not support (a retrieving section for detecting whether or not there is a section for performing an operation). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Newell since Newell provides a method in which devices in a network can inform other devices of network capabilities, allowing devices to make appropriate decision when routing requests, allowing the system of the '692 reference to performing routing based on the capabilities of other devices.

French teaches in paragraphs [0227] and [0275], assigned VPN IDs are stored as updated information within network objects, and a VPN creator ensures unique VPN IDs are created such that duplicate addresses can exist within a VPN that has an assigned VPN ID, and a server generates an IP address on behalf of its client (a generating section for generating an IP address and a VPNID to a user's device, and a registering section for registering an IP address and a VPNID generated by a generating section and information used by a user's device to which an IP address and a VPNIS are added). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of French since French provides a system of maintaining and updating VPN IDs for IP addresses within virtual private networks, allowing the optical network of the '692 reference to provide optical VPN services to customers and provide the privacy, robustness, and cost effectiveness of virtual private networks.

Morinaga teaches in column 5, line 60 through column 6, line 6, and in column 7, lines 45-59, and in FIG. 2, Sheet 2 of 9, a H.323 protocol portion (item 33, FIG. 2), a CODEC (item 34, FIG. 2), and a call control portion (item 31, FIG. 2), that operate where a transmission format to be used in accordance with each user information of a calling side is registered as a circuit, and a CODEC to be used in accordance with each user information of the calling side is registered as the CODEC, and if the user information of a calling side is accompanied by ON flag in the target parameter setting table, the reference table of the user information of the calling side and communication method is looked up, so that the transmission format to be used as the communication



method is decided, and, in column 9, lines 41-54, and in FIG. 3, Sheet 3 of 9, a gateway receives a calling signal and a target parameter setting a table is looked up as to judge parameters (a detection section for detecting whether or not a user's device is connected, and a receiving and determining section for receiving a test signal which is transmitted via a data channel by using an identifier from a user's device and determining a first signal format type which belongs to a user's device). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Morinaga since Morinaga teaches a system that involves storing user information and transmission parameters, allowing the system of the '692 reference to be able to adjust routing parameters that best serve a user's preferences or QoS requirements.

**In regards to Claim 29**, as discussed in the rejection of Claim 27, the '692 reference teaches a converting section and an alternate converting operation. The '692 reference further teaches an operation in a user's own device. The '692 reference further teaches in paragraph [0008], page 3, lines 17-19, optical transport network data entities are clients of SDH or SONET, implicitly teaching the components of these entities are already treated as clients in the optical network and can be implemented in client equipment (an operation in a user's own device).

**In regards to Claim 33**, the '692 reference teaches in paragraph [0005], page 2, lines 40-43, 48-49 and 52-55, an optical transport network is intended to be a multi-

service network that supports a wide variety of layers including SDH STM-N, SONET, ATM, IP, as well as other formats, to provide a universal transport medium for high bandwidth services, where client signals are mapped into the payload area of a frame structure called an optical transport unit (OUT), and where the payload to be carried from the client, i.e. the client signal, which may be ATM, SDH, STM-N, or IP, is mapped into an optical payload unit (OPU), and, in paragraph [0019], page 5, lines 50-55, and in Fig. 1, page 18, a node N1 (Fig. 1), a node SNA (Fig. 1), a node SNB (Fig. 1), and a node N1 (Fig. 1) at the edges a conventional SDH network (optical network, and a plurality of converting sections, which are disposed so as to correspond to plural different first signal formats, for converting a first signal format and a second signal format alternatively under conditions in which the first signal format is used by a user's device and a second signal format which is used in the network are different from each other, and a terminating device for containing the user's device, and performing alternate converting operations).

The '692 reference fails to teach a retrieving section for detecting whether or not there is a section for performing an operation, a notifying section to determine whether or not a format is used by another device and notify that the formats do not coincide each other for setting up a service to a user's device, a generating section for generating an IP address and a VPNID to a user's device, and a registering section for registering an IP address and a VPNID generated by a generating section and information used by a user's device to which an IP address and a VPNIS are added, and a receiving and determining section for receiving a test signal which is transmitted

via a data channel by using an identifier from a user's device and determining a first signal format type which belongs to a user's device.

Newell teaches in column 4, lines 11-27, devices exchange information concerning which protocol feature teaches does or does not support (a retrieving section for detecting whether or not there is a section for performing an operation). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Newell since Newell provides a method in which devices in a network can inform other devices of network capabilities, allowing devices to make appropriate decision when routing requests, allowing the system of the '692 reference to performing routing based on the capabilities of other devices.

Newell teaches in column 4, lines 11-27, devices exchange information concerning which protocol feature each does or does not support (a notifying section to determine whether or not a format is used by another device and notify that the formats do not coincide each other for setting up a service to a user's device). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Newell since Newell provides a method in which devices in a network can inform other devices of network capabilities, allowing devices to make appropriate decision when routing requests, allowing the system of the '692 reference to performing routing based on the capabilities of other devices.

French teaches in paragraphs [0227] and [0275], assigned VPN IDs are stored as updated information within network objects, and a VPN creator ensures unique VPN IDs are created such that duplicate addresses can exist within a VPN that has an assigned VPN ID, and a server generates an IP address on behalf of its client (a generating section for generating an IP address and a VPNID to a user's device, and a registering section for registering an IP address and a VPNID generated by a generating section and information used by a user's device to which an IP address and a VPNIS are added). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of French since French provides a system of maintaining and updating VPN IDs for IP addresses within virtual private networks, allowing the optical network of the '692 reference to provide optical VPN services to customers and provide the privacy, robustness, and cost effectiveness of virtual private networks.

Morinaga teaches in column 5, line 60 through column 6, line 6, and in column 7, lines 45-59, and in FIG. 2, Sheet 2 of 9, a H.323 protocol portion (item 33, FIG. 2), a CODEC (item 34, FIG. 2), and a call control portion (item 31, FIG. 2), that operate where a transmission format to be used in accordance with each user information of a calling side is registered as a circuit, and a CODEC to be used in accordance with each user information of the calling side is registered as the CODEC, and if the user information of a calling side is accompanied by ON flag in the target parameter setting table, the reference table of the user information of the calling side and communication method is looked up, so that the transmission format to be used as the communication

method is decided, and, in column 9, lines 41-54, and in FIG. 3, Sheet 3 of 9, a gateway receives a calling signal and a target parameter setting a table is looked up as to judge parameters (a receiving and determining section for receiving a test signal which is transmitted via a data channel by using an identifier from a user's device and determining a first signal format type which belongs to a user's device). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Morinaga since Morinaga teaches a system that involves storing user information and transmission parameters, allowing the system of the '692 reference to be able to adjust routing parameters that best serve a user's preferences or QoS requirements.

**In regards to Claim 48**, as discussed in the rejection of Claim 13, the '692 reference in view of Newell and French teaches an OVPN system.

The '692 reference fails to teach a receiving and transmitting section for receiving a notice that a user's device is connected to a base point device via a control channel from a base point device which is disposed between a user's device and a network, and transmitting an IP address and a VPNID which are allocated to a user's device according to a base point device.

Morinaga teaches in column 5, line 60 through column 6, line 6, and in column 7, lines 45-59, and in FIG. 2, Sheet 2 of 9, a H.323 protocol portion (item 33, FIG. 2), a CODEC (item 34, FIG. 2), and a call control portion (item 31, FIG. 2), that operate where a transmission format to be used in accordance with each user information of a

calling side is registered as a circuit, and a CODEC to be used in accordance with each user information of the calling side is registered as the CODEC, and if the user information of a calling side is accompanied by ON flag in the target parameter setting table, the reference table of the user information of the calling side and communication method is looked up, so that the transmission format to be used as the communication method is decided, and, in column 9, lines 41-54, and in FIG. 3, Sheet 3 of 9, a gateway receives a calling signal and a target parameter setting a table is looked up as to judge parameters (a receiving and transmitting section for receiving a notice that a user's device is connected to a base point device via a control channel from a base point device which is disposed between a user's device and a network). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Morinaga since Morinaga teaches a system that involves storing user information and transmission parameters, allowing the system of the '692 reference to be able to adjust routing parameters that best serve a user's preferences or QoS requirements.

French teaches in paragraphs [0227] and [0275], assigned VPN IDs are stored as updated information within network objects, and a VPN creator ensures unique VPN IDs are created such that duplicate addresses can exist within a VPN that has an assigned VPN ID, and a server generates an IP address on behalf of its client (transmitting an IP address and a VPNID which are allocated to a user's device according to a base point device). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with

the invention of French since French provides a system of maintaining and updating VPN IDs for IP addresses within virtual private networks, allowing the optical network of the '692 reference to provide optical VPN services to customers and provide the privacy, robustness, and cost effectiveness of virtual private networks.

**In regards to Claim 57**, as discussed in the rejection of Claim 13, the '692 reference in view of Newell and French teaches an OVPN system.

The '692 reference fails to teach a receiving and transmitting section for receiving a notice that a user's device is connected to a base point device via a control channel from a base point device which is disposed between a user's device and a network, and transmitting an IP address and a VPNID which are allocated to a user's device according to a base point device.

Morinaga teaches in column 5, line 60 through column 6, line 6, and in column 7, lines 45-59, and in FIG. 2, Sheet 2 of 9, a H.323 protocol portion (item 33, FIG. 2), a CODEC (item 34, FIG. 2), and a call control portion (item 31, FIG. 2), that operate where a transmission format to be used in accordance with each user information of a calling side is registered as a circuit, and a CODEC to be used in accordance with each user information of the calling side is registered as the CODEC, and if the user information of a calling side is accompanied by ON flag in the target parameter setting table, the reference table of the user information of the calling side and communication method is looked up, so that the transmission format to be used as the communication method is decided, and, in column 9, lines 41-54, and in FIG. 3, Sheet 3 of 9, a gateway

receives a calling signal and a target parameter setting a table is looked up as to judge parameters (a receiving and transmitting section for receiving a notice that a user's device is connected to a base point device via a control channel from a base point device which is disposed between a user's device and a network). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Morinaga since Morinaga teaches a system that involves storing user information and transmission parameters, allowing the system of the '692 reference to be able to adjust routing parameters that best serve a user's preferences or QoS requirements.

French teaches in paragraphs [0227] and [0275], assigned VPN IDs are stored as updated information within network objects, and a VPN creator ensures unique VPN IDs are created such that duplicate addresses can exist within a VPN that has an assigned VPN ID, and a server generates an IP address on behalf of its client (transmitting an IP address and a VPNID which are allocated to a user's device according to a base point device). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of French since French provides a system of maintaining and updating VPN IDs for IP addresses within virtual private networks, allowing the optical network of the '692 reference to provide optical VPN services to customers and provide the privacy, robustness, and cost effectiveness of virtual private networks.



**Claim 17** is rejected under 35 U.S.C. 103(a) as being unpatentable over the '692 reference in view of Newell, French, and Jurkevich et al. (Patent Number: 5,282,207), hereafter referred to as Jurkevich.

**In regards to Claim 17**, as discussed in the rejection of Claim 13, the '692 reference in view of Newell and French teaches a converting section for performing an alternate converting operation and a retrieving result by a retrieving section indicates that there is not a section for performing alternate converting operation and generating an IP address and a VPNID for a user's device.

The '692 reference fails to teach an inquiring section for inquiring whether or not it is possible to change a vacant section to user's device which is under operation, and a requesting a generating section for requesting for changing a section for performing alternate operation to other user device.

Jurkevich teaches in column 37, lines 36-60, certain links experiencing server congestion may cause a request to change a format to send data on new bandwidth, and if a request from more bandwidth is approved, additional bandwidth is allocated as requested (an inquiring section for inquiring whether or not it is possible to change a vacant section to user's device which is under operation, and a requesting a generating section for requesting for changing a section for performing alternate operation to other user device). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Jurkevich since Jurkevich provides a method of acquiring new network resources when previous network resource become inadequate, allowing the system of the '692

reference to adjust to new users attempting to establish connections and send data and for current users that are changing their data rate requirements.

**Claim 28** is rejected under 35 U.S.C. 103(a) as being unpatentable over the '692 reference in view of Newell, French, Morinaga, and further in view of Oguchi.

**In regards to Claim 28**, as discussed in the rejections of Claim 27, the '692 reference in view of Newell, French, and Morinaga teaches a registering section and a user's own device which corresponds to a first signal format type used in the user's device.

The '692 reference fails to teach a port identifier.

Oguchi teaches in paragraphs [0045] and [0202], a virtual router correspondence table that includes port numbers (a port identifier). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Oguchi since Oguchi provides a method of establishing a virtual network and distributing the necessary information to establish and maintain such a virtual network, allowing the optical network of the '692 reference to provide optical VPN services to customers and provide the privacy, robustness, and cost effectiveness of virtual private networks.

**Claims 40 and 47** is rejected under 35 U.S.C. 103(a) as being unpatentable over the '692 reference in view of Newell, French, and further in view of Oguchi.

**In regards to Claim 40**, the '692 reference teaches in paragraph [0005], page 2, lines 40-43, 48-49 and 52-55, an optical transport network is intended to be a multi-service network that supports a wide variety of layers including SDH STM-N, SONET, ATM, IP, as well as other formats, to provide a universal transport medium for high bandwidth services, where client signals are mapped into the payload area of a frame structure called an optical transport unit (OUT), and where the payload to be carried from the client, i.e. the client signal, which may be ATM, SDH, STM-N, or IP, is mapped into an optical payload unit (OPU), and, in paragraph [0019], page 5, lines 50-55, and in Fig. 1, page 18, a node N1 (Fig. 1), a node SNA (Fig. 1), a node SNB (Fig. 1), and a node N1 (Fig. 1) at the edges a conventional SDH network (a transmitting section for transmitting a first signal format which is transmitted from a user's device to an optical network by encapsulating a first signal format by a second signal format, and a transmitting section for transmitting an encapsulated signal which is encapsulated by a second signal format which is transmitted from an optical network to a user's device by de-encapsulating to a first signal format, and a terminating device for containing the user's device). The '692 reference fails to teach VPN. Oguchi teaches VPN.

Oguchi teaches in paragraph [0065], [0067], [0083], [0085], and [0143], virtual routers having the same VPN-ID exchange routing information though a level-2 tunnel established between edge routers, which can involves a host having an IP address, and then generate routing tables for that VPN-ID (VPN). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Oguchi since Oguchi provides a method of establishing a

virtual network and distributing the necessary information to establish and maintain such a virtual network, allowing the optical network of the '692 reference to provide optical VPN services to customers and provide the privacy, robustness, and cost effectiveness of virtual private networks.

**In regards to Claim 47**, the '692 reference teaches in paragraph [0005], page 2, lines 40-43, 48-49 and 52-55, an optical transport network is intended to be a multi-service network that supports a wide variety of layers including SDH STM-N, SONET, ATM, IP, as well as other formats, to provide a universal transport medium for high bandwidth services, where client signals are mapped into the payload area of a frame structure called an optical transport unit (OUT), and where the payload to be carried from the client, i.e. the client signal, which may be ATM, SDH, STM-N, or IP, is mapped into an optical payload unit (OPU), and, in paragraph [0019], page 5, lines 50-55, and in Fig. 1, page 18, a node N1 (Fig. 1), a node SNA (Fig. 1), a node SNB (Fig. 1), and a node N1 (Fig. 1) at the edges a conventional SDH network (optical network, and a plurality of converting sections, which are disposed so as to correspond to plural different first signal formats, for converting a first signal format and a second signal format alternatively under conditions in which the first signal format is used by a user's device and a second signal format which is used in the network are different from each other, and a terminating device for containing the user's device, and performing alternate converting operations).

The '692 reference teaches in paragraph [0005], page 2, lines 40-43, 48-49 and 52-55, an optical transport network is intended to be a multi-service network that supports a wide variety of layers including SDH STM-N, SONET, ATM, IP, as well as other formats, to provide a universal transport medium for high bandwidth services, where client signals are mapped into the payload area of a frame structure called an optical transport unit (OUT), and where the payload to be carried from the client, i.e. the client signal, which may be ATM, SDH, STM-N, or IP, is mapped into an optical payload unit (OPU), and, in paragraph [0019], page 5, lines 50-55, and in Fig. 1, page 18, a node N1 (Fig. 1), a node SNA (Fig. 1), a node SNB (Fig. 1), and a node N1 (Fig. 1) at the edges a conventional SDH network (a transmitting section for transmitting a first signal format which is transmitted from a user's device to an optical network by encapsulating a first signal format by a second signal format, and a transmitting section for transmitting an encapsulated signal which is encapsulated by a second signal format which is transmitted from an optical network to a user's device by de-encapsulating to a first signal format, and a terminating device for containing the user's device).

The '692 reference fails to teach a retrieving section for detecting whether or not there is a section for performing an operation, a notifying section to determine whether or not a format is used by another device and notify that the formats do not coincide each other for setting up a service to a user's device, a generating section for generating an IP address and a VPNID to a user's device, and a registering section for registering an IP address and a VPNID generated by a generating section and

information used by a user's device to which an IP address and a VPNIS are added, and VPN.

Newell teaches in column 4, lines 11-27, devices exchange information concerning which protocol feature teaches does or does not support (a retrieving section for detecting whether or not there is a section for performing an operation). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Newell since Newell provides a method in which devices in a network can inform other devices of network capabilities, allowing devices to make appropriate decision when routing requests, allowing the system of the '692 reference to performing routing based on the capabilities of other devices.

Newell teaches in column 4, lines 11-27, devices exchange information concerning which protocol feature each does or does not support (a notifying section to determine whether or not a format is used by another device and notify that the formats do not coincide each other for setting up a service to a user's device). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Newell since Newell provides a method in which devices in a network can inform other devices of network capabilities, allowing devices to make appropriate decision when routing requests, allowing the system of the '692 reference to performing routing based on the capabilities of other devices.

French teaches in paragraphs [0227] and [0275], assigned VPN IDs are stored as updated information within network objects, and a VPN creator ensures unique VPN IDs are created such that duplicate addresses can exist within a VPN that has an assigned VPN ID, and a server generates an IP address on behalf of its client (a generating section for generating an IP address and a VPNID to a user's device, and a registering section for registering an IP address and a VPNID generated by a generating section and information used by a user's device to which an IP address and a VPNIS are added). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of French since French provides a system of maintaining and updating VPN IDs for IP addresses within virtual private networks, allowing the optical network of the '692 reference to provide optical VPN services to customers and provide the privacy, robustness, and cost effectiveness of virtual private networks.

Oguchi teaches in paragraph [0065], [0067], [0083], [0085], and [0143], virtual routers having the same VPN-ID exchange routing information though a level-2 tunnel established between edge routers, which can involves a host having an IP address, and then generate routing tables for that VPN-ID (VPN). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Oguchi since Oguchi provides a method of establishing a virtual network and distributing the necessary information to establish and maintain such a virtual network, allowing the optical network of the '692 reference to provide optical

VPN services to customers and provide the privacy, robustness, and cost effectiveness of virtual private networks.

**Claim 43 and 46** are rejected under 35 U.S.C. 103(a) as being unpatentable over the '692 reference in view of Oguchi.

**In regards to Claims 43 and 46**, the '692 reference teaches in paragraph [0005], page 2, lines 40-43, 48-49 and 52-55, an optical transport network is intended to be a multi-service network that supports a wide variety of layers including SDH STM-N, SONET, ATM, IP, as well as other formats, to provide a universal transport medium for high bandwidth services, where client signals are mapped into the payload area of a frame structure called an optical transport unit (OUT), and where the payload to be carried fro the client, i.e. the client signal, which may be ATM, SDH, STM-N, or IP, is mapped into an optical payload unit (OPU), and, in paragraph [0019], page 5, lines 50-55, and in Fig. 1, page 18, a node N1 (Fig. 1), a node SNA (Fig. 1), a node SNB (Fig. 1), and a node N1 (Fig. 1) at the edges a conventional SDH network (optical network, and a plurality of converting sections, which are disposed so as to correspond to plural different first signal formats, for converting a first signal format and a second signal format alternatively under conditions in which the first signal format is used by a user's device and a second signal format which is used in the network are different from each other, a transmitting section for transmitting a first signal format which is transmitted from a user's device to an optical network by encapsulating a first signal format by a second signal format, and a transmitting section for transmitting an encapsulated signal



which is encapsulated by a second signal format which is transmitted from an optical network to a user's device by de-encapsulating to a first signal format, and a terminating device for containing the user's device).

The '692 reference fails to teach VPN.

Oguchi teaches in paragraph [0065], [0067], [0083], [0085], and [0143], virtual routers having the same VPN-ID exchange routing information through a level-2 tunnel established between edge routers, which can involve a host having an IP address, and then generate routing tables for that VPN-ID (VPN). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Oguchi since Oguchi provides a method of establishing a virtual network and distributing the necessary information to establish and maintain such a virtual network, allowing the optical network of the '692 reference to provide optical VPN services to customers and provide the privacy, robustness, and cost effectiveness of virtual private networks.

**Claims 41, 42, 44 and 45** are rejected under 35 U.S.C. 103(a) as being unpatentable over the '692 reference in view of Oguchi, and further in view of Takagi.

**In regards to Claim 41 and 44**, as discussed in the rejections of Claim 40 and 43, the '692 reference in view of Oguchi teaches a transmitting section to an OVPN.

The '692 reference fails to teach a multiplying section for multiplying a plurality of signals according to a second signal format.

Takagi teaches in paragraphs [0076] through [0084], and in FIG. 1, FIG. 2, FIG. 3, and FIG. 4, a system where a multiple ATM cells are combined and processed and encapsulated for transmission through an optical fiber to a single base station, and where a base station extracts the multiple ATM cells from the encapsulation (a multiplying section for multiplying a plurality of signals by a second signal format which are directed to a common destination, and a transmitting section to a user's device is provided with a separating section for the multiplied signal by the multiplying section into a plurality of signals). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Takagi since Takagi teaches a detailed method of combining data unit prior to encapsulation and transmission across an optical transmission medium so that transmission speeds are maintained, which can be incorporated into the system of the '692 reference so that overhead is reduced and transmission speeds are maintained across an optical network.

**In regards to Claim 42 and 45**, as discussed in the rejections of Claim 40 and 43, the '692 reference in view of Oguchi teaches a transmitting section to an OVPN.

The '692 reference fails to teach a dividing and encapsulating section for dividing and encapsulating a series of signals according to a first signal format into a plurality of signals according to a second signal format.

Takagi teaches in paragraphs [0076] through [0084], and in FIG. 1, FIG. 2, FIG. 3, and FIG. 4, a system where a multiple ATM cells are combined and processed and

encapsulated for transmission through an optical fiber to a single base station, and where a base station extracts the multiple ATM cells from the encapsulation (a dividing and encapsulating section for dividing and encapsulating a series of signals according to a first signal format into a plurality of signals according to a second signal format). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Takagi since Takagi teaches a detailed method of combining data unit prior to encapsulation and transmission across an optical transmission medium so that transmission speeds are maintained, which can be incorporated into the system of the '692 reference so that overhead is reduced and transmission speeds are maintained across an optical network.

**Claims 21, 30, 49, 50, 52, 53, 54 and 56** are rejected under 35 U.S.C. 103(a) as being unpatentable over the '692 reference in view of Morinaga and French.

**In regards to Claim 21**, the '692 reference teaches in paragraph [0005], page 2, lines 40-43, 48-49 and 52-55, an optical transport network is intended to be a multi-service network that supports a wide variety of layers including SDH STM-N, SONET, ATM, IP, as well as other formats, to provide a universal transport medium for high bandwidth services, where client signals are mapped into the payload area of a frame structure called an optical transport unit (OUT), and where the payload to be carried from the client, i.e. the client signal, which may be ATM, SDH, STM-N, or IP, is mapped into an optical payload unit (OPU), and, in paragraph [0019], page 5, lines 50-55, and in

Fig. 1, page 18, a node N1 (Fig. 1), a node SNA (Fig. 1), a node SNB (Fig. 1), and a node N1 (Fig. 1) at the edges a conventional SDH network (a transmitting section for transmitting a first type information). The '692 reference fails to teach a determining section for determining a first signal format type which is used in a user's device, format type information which is determined by a determining section, and a maintaining section for maintaining a plurality of generated IP address, a VPNIS, and a first signal format type information.

Morinaga teaches in column 5, line 60 through column 6, line 6, and in column 7, lines 45-59, and in FIG. 2, Sheet 2 of 9, a H.323 protocol portion (item 33, FIG. 2), a CODEC (item 34, FIG. 2), and a call control portion (item 31, FIG. 2), that operate where a transmission format to be used in accordance with each user information of a calling side is registered as a circuit, and a CODEC to be used in accordance with each user information of the calling side is registered as the CODEC, and if the user information of a calling side is accompanied by ON flag in the target parameter setting table, the reference table of the user information of the calling side and communication method is looked up, so that the transmission format to be used as the communication method is decided, and, in column 9, lines 41-54, and in FIG. 3, Sheet 3 of 9, a gateway receives a calling signal and a target parameter setting a table is looked up as to judge parameters (a determining section for determining a first signal format type which is used in a user's device, format type information which is determined by a determining section). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Morinaga

since Morinaga teaches a system that involves storing user information and transmission parameters, allowing the system of the '692 reference to be able to adjust routing parameters that best serve a user's preferences or QoS requirements.

French teaches in paragraphs [0227] and [0275], assigned VPN IDs are stored as updated information within network objects, and a VPN creator ensures unique VPN IDs are created such that duplicate addresses can exist within a VPN that has an assigned VPN ID, and a server generates an IP address on behalf of its client (a maintaining section for maintaining a plurality of generated IP address, a VPNIS, and a first signal format type information). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of French since French provides a system of maintaining and updating VPN IDs for IP addresses within virtual private networks, allowing the optical network of the '692 reference to provide optical VPN services to customers and provide the privacy, robustness, and cost effectiveness of virtual private networks.

**In regards to Claim 30**, the '692 reference teaches in paragraph [0005], page 2, lines 40-43, 48-49 and 52-55, an optical transport network is intended to be a multi-service network that supports a wide variety of layers including SDH STM-N, SONET, ATM, IP, as well as other formats, to provide a universal transport medium for high bandwidth services, where client signals are mapped into the payload area of a frame structure called an optical transport unit (OUT), and where the payload to be carried from the client, i.e. the client signal, which may be ATM, SDH, STM-N, or IP, is mapped into

an optical payload unit (OPU), and, in paragraph [0019], page 5, lines 50-55, and in Fig. 1, page 18, a node N1 (Fig. 1), a node SNA (Fig. 1), a node SNB (Fig. 1), and a node N1 (Fig. 1) at the edges a conventional SDH network (optical network, and a plurality of converting sections, which are disposed so as to correspond to plural different first signal formats, for converting a first signal format and a second signal format alternatively under conditions in which the first signal format is used by a user's device and a second signal format which is used in the network are different from each other, and a terminating device for containing the user's device, and performing alternate converting operations).

The '692 reference fails to teach a detection section for detecting whether or not a user's device is connected to a base point, a receiving and maintaining section for receiving an IP address and a VPNID which are added to a base point device via a control channel from a OVPN terminating device.

Morinaga teaches in column 5, line 60 through column 6, line 6, and in column 7, lines 45-59, and in FIG. 2, Sheet 2 of 9, a H.323 protocol portion (item 33, FIG. 2), a CODEC (item 34, FIG. 2), and a call control portion (item 31, FIG. 2), that operate where a transmission format to be used in accordance with each user information of a calling side is registered as a circuit, and a CODEC to be used in accordance with each user information of the calling side is registered as the CODEC, and if the user information of a calling side is accompanied by ON flag in the target parameter setting table, the reference table of the user information of the calling side and communication method is looked up, so that the transmission format to be used as the communication

method is decided, and, in column 9, lines 41-54, and in FIG. 3, Sheet 3 of 9, a gateway receives a calling signal and a target parameter setting a table is looked up as to judge parameters (a detection section for detecting whether or not a user's device is connected to a base point). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Morinaga since Morinaga teaches a system that involves storing user information and transmission parameters, allowing the system of the '692 reference to be able to adjust routing parameters that best serve a user's preferences or QoS requirements.

French teaches in paragraphs [0227] and [0275], assigned VPN IDs are stored as updated information within network objects, and a VPN creator ensures unique VPN IDs are created such that duplicate addresses can exist within a VPN that has an assigned VPN ID, and a server generates an IP address on behalf of its client (a receiving and maintaining section for receiving an IP address and a VPNID which are added to a base point device via a control channel from a OVPN terminating device). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of French since French provides a system of maintaining and updating VPN IDs for IP addresses within virtual private networks, allowing the optical network of the '692 reference to provide optical VPN services to customers and provide the privacy, robustness, and cost effectiveness of virtual private networks.

**In regards to Claim 49**, the '692 reference teaches in paragraph [0005], page 2, lines 40-43, 48-49 and 52-55, an optical transport network is intended to be a multi-service network that supports a wide variety of layers including SDH STM-N, SONET, ATM, IP, as well as other formats, to provide a universal transport medium for high bandwidth services, where client signals are mapped into the payload area of a frame structure called an optical transport unit (OUT), and where the payload to be carried from the client, i.e. the client signal, which may be ATM, SDH, STM-N, or IP, is mapped into an optical payload unit (OPU), and, in paragraph [0019], page 5, lines 50-55, and in Fig. 1, page 18, a node N1 (Fig. 1), a node SNA (Fig. 1), a node SNB (Fig. 1), and a node N1 (Fig. 1) at the edges a conventional SDH network (optical network, and a plurality of converting sections, which are disposed so as to correspond to plural different first signal formats, for converting a first signal format and a second signal format alternatively under conditions in which the first signal format is used by a user's device and a second signal format which is used in the network are different from each other, a transmitting section for transmitting a first signal format which is transmitted from a user's device to an optical network by encapsulating a first signal format by a second signal format, and a transmitting section for transmitting an encapsulated signal which is encapsulated by a second signal format which is transmitted from an optical network to a user's device by de-encapsulating to a first signal format, and a terminating device for containing the user's device).

The '692 reference fails to teach a receiving and transmitting section for receiving a notice that a user's device is connected to a base point device via a control channel



from a base point device which is disposed between a user's device and a network, VPN, and transmitting an IP address and a VPNID which are allocated to a user's device according to a base point device.

Morinaga teaches in column 5, line 60 through column 6, line 6, and in column 7, lines 45-59, and in FIG. 2, Sheet 2 of 9, a H.323 protocol portion (item 33, FIG. 2), a CODEC (item 34, FIG. 2), and a call control portion (item 31, FIG. 2), that operate where a transmission format to be used in accordance with each user information of a calling side is registered as a circuit, and a CODEC to be used in accordance with each user information of the calling side is registered as the CODEC, and if the user information of a calling side is accompanied by ON flag in the target parameter setting table, the reference table of the user information of the calling side and communication method is looked up, so that the transmission format to be used as the communication method is decided, and, in column 9, lines 41-54, and in FIG. 3, Sheet 3 of 9, a gateway receives a calling signal and a target parameter setting a table is looked up as to judge parameters (a receiving and transmitting section for receiving a notice that a user's device is connected to a base point device via a control channel from a base point device which is disposed between a user's device and a network). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Morinaga since Morinaga teaches a system that involves storing user information and transmission parameters, allowing the system of the '692 reference to be able to adjust routing parameters that best serve a user's preferences or QoS requirements.

French teaches in paragraphs [0227] and [0275], assigned VPN IDs are stored as updated information within network objects, and a VPN creator ensures unique VPN IDs are created such that duplicate addresses can exist within a VPN that has an assigned VPN ID, and a server generates an IP address on behalf of its client (transmitting an IP address and a VPNID which are allocated to a user's device according to a base point device). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of French since French provides a system of maintaining and updating VPN IDs for IP addresses within virtual private networks, allowing the optical network of the '692 reference to provide optical VPN services to customers and provide the privacy, robustness, and cost effectiveness of virtual private networks.

**In regards to Claim 50**, as discussed in the rejection of Claim 49, the '692 reference in view of Morinaga and French teaches a receiving section and a transmitting section, a base point device, and an IP address and a VPNID.

The '692 reference fails to teach receiving a receipt confirmation, and transmitting a final connection confirmation for notifying the receipt of a receipt confirmation.

Morinaga further teaches in column 11, lines 50-56, and in column 12, lines 19-25, and in FIG. 5, Sheet 5 of 9, in step #301 (FIG. 5) a RECEPTION OF SETUP occurs, and then, in the connection process step # 311 (FIG. 5), a TRANSMISSION OF CONN is received, and then a transmission of RECEPTION OF CONN-ACK (receiving a

receipt confirmation, and transmitting a final connection confirmation for notifying the receipt of a receipt confirmation). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Morinaga since Morinaga teaches a system that involves storing user information and transmission parameters, allowing the system of the '692 reference to be able to adjust routing parameters that best serve a user's preferences or QoS requirements.

**In regards to Claim 52**, as discussed in the rejection of Claim 49, the '692 reference in view of Morinaga and French teaches an OVPN terminating device.

The '692 reference fails to teach a section for performing an alternate converting operation.

Morinaga teaches in column 5, line 60 through column 6, line 6, and in column 7, lines 45-59, and in FIG. 2, Sheet 2 of 9, a H.323 protocol portion (item 33, FIG. 2), a CODEC (item 34, FIG. 2), and a call control portion (item 31, FIG. 2), that operate where a transmission format to be used in accordance with each user information of a calling side is registered as a circuit, and a CODEC to be used in accordance with each user information of the calling side is registered as the CODEC, and if the user information of a calling side is accompanied by ON flag in the target parameter setting table, the reference table of the user information of the calling side and communication method is looked up, so that the transmission format to be used as the communication method is decided (a section for performing an alternate converting operation). It would

have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Morinaga since Morinaga teaches a system that involves storing user information and transmission parameters, allowing the system of the '692 reference to be able to adjust routing parameters that best serve a user's preferences or QoS requirements.

**In regards to Claim 53**, the '692 reference teaches in paragraph [0005], page 2, lines 40-43, 48-49 and 52-55, an optical transport network is intended to be a multi-service network that supports a wide variety of layers including SDH STM-N, SONET, ATM, IP, as well as other formats, to provide a universal transport medium for high bandwidth services, where client signals are mapped into the payload area of a frame structure called an optical transport unit (OUT), and where the payload to be carried from the client, i.e. the client signal, which may be ATM, SDH, STM-N, or IP, is mapped into an optical payload unit (OPU), and, in paragraph [0019], page 5, lines 50-55, and in Fig. 1, page 18, a node N1 (Fig. 1), a node SNA (Fig. 1), a node SNB (Fig. 1), and a node N1 (Fig. 1) at the edges a conventional SDH network (a transmitting section for transmitting a first signal format type information which is used by a user's device and an IP address to an OVPN terminating device).

The '692 reference fails to teach a detection section for detecting whether or not a user's device is connected to a base point, a notifying section for notifying an OVPN terminating device via a control channel that it is detected that a user's device is connected to a base point device, a transmitting section for transmitting a receipt

confirmation that a receiving section received an IP address and a VPNID to an OVPN terminating device, and a receiving section for receiving an IP address and a VPNID which are allocated to a user's device from an OVPN terminating device via a control channel.

Morinaga teaches in column 5, line 60 through column 6, line 6, and in column 7, lines 45-59, and in FIG. 2, Sheet 2 of 9, a H.323 protocol portion (item 33, FIG. 2), a CODEC (item 34, FIG. 2), and a call control portion (item 31, FIG. 2), that operate where a transmission format to be used in accordance with each user information of a calling side is registered as a circuit, and a CODEC to be used in accordance with each user information of the calling side is registered as the CODEC, and if the user information of a calling side is accompanied by ON flag in the target parameter setting table, the reference table of the user information of the calling side and communication method is looked up, so that the transmission format to be used as the communication method is decided, and, in column 9, lines 41-54, and in FIG. 3, Sheet 3 of 9, a gateway receives a calling signal and a target parameter setting a table is looked up as to judge parameters (a detection section for detecting whether or not a user's device is connected to a base point).

Morinaga teaches in column 5, line 60 through column 6, line 6, and in column 7, lines 45-59, and in FIG. 2, Sheet 2 of 9, a H.323 protocol portion (item 33, FIG. 2), a CODEC (item 34, FIG. 2), and a call control portion (item 31, FIG. 2), that operate where a transmission format to be used in accordance with each user information of a calling side is registered as a circuit, and a CODEC to be used in accordance with each

user information of the calling side is registered as the CODEC, and if the user information of a calling side is accompanied by ON flag in the target parameter setting table, the reference table of the user information of the calling side and communication method is looked up, so that the transmission format to be used as the communication method is decided, and, in column 9, lines 41-54, and in FIG. 3, Sheet 3 of 9, a gateway receives a calling signal and a target parameter setting a table is looked up as to judge parameters (a notifying section for notifying an OVPN terminating device via a control channel that it is detected that a user's device is connected to a base point device). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Morinaga since Morinaga teaches a system that involves storing user information and transmission parameters, allowing the system of the '692 reference to be able to adjust routing parameters that best serve a user's preferences or QoS requirements.

Morinaga further teaches in column 11, lines 50-56, and in column 12, lines 19-25, and in FIG. 5, Sheet 5 of 9, in step #301 (FIG. 5) a RECEPTION OF SETUP occurs, and then, in the connection process step # 311 (FIG. 5), a TRANSMISSION OF CONN is received, and then a transmission of RECEPTION OF CONN-ACK (a transmitting section for transmitting a receipt confirmation that a receiving section received an IP address and a VPNID to an OVPN terminating device). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Morinaga since Morinaga teaches a system that involves storing user information and transmission parameters, allowing the system of

the '692 reference to be able to adjust routing parameters that best serve a user's preferences or QoS requirements.

French teaches in paragraphs [0227] and [0275], assigned VPN IDs are stored as updated information within network objects, and a VPN creator ensures unique VPN IDs are created such that duplicate addresses can exist within a VPN that has an assigned VPN ID, and a server generates an IP address on behalf of its client (a receiving section for receiving an IP address and a VPNID which are allocated to a user's device from an OVPN terminating device via a control channel). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of French since French provides a system of maintaining and updating VPN IDs for IP addresses within virtual private networks, allowing the optical network of the '692 reference to provide optical VPN services to customers and provide the privacy, robustness, and cost effectiveness of virtual private networks.

**In regards to Claim 54**, as discussed in the rejection of Claim 53, the '692 reference in view of Morinaga and French teaches a base point device.

The '692 reference fails to teach a determining section for determining a first signal format type information which is employed in a user's device, and a transmitting device for transmitting a format type information which is determined by a determining section to an OVPN terminating device.

Morinaga teaches in column 5, line 60 through column 6, line 6, and in column 7, lines 45-59, and in FIG. 2, Sheet 2 of 9, a H.323 protocol portion (item 33, FIG. 2), a CODEC (item 34, FIG. 2), and a call control portion (item 31, FIG. 2), that operate where a transmission format to be used in accordance with each user information of a calling side is registered as a circuit, and a CODEC to be used in accordance with each user information of the calling side is registered as the CODEC, and if the user information of a calling side is accompanied by ON flag in the target parameter setting table, the reference table of the user information of the calling side and communication method is looked up, so that the transmission format to be used as the communication method is decided, and, in column 9, lines 41-54, and in FIG. 3, Sheet 3 of 9, a gateway receives a calling signal and a target parameter setting a table is looked up as to judge parameters (a determining section for determining a first signal format type information which is employed in a user's device). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Morinaga since Morinaga teaches a system that involves storing user information and transmission parameters, allowing the system of the '692 reference to be able to adjust routing parameters that best serve a user's preferences or QoS requirements.

Morinaga teaches in column 5, line 60 through column 6, line 6, and in column 7, lines 45-59, and in column 12, lines 18-25, and in FIG. 2, Sheet 2 of 9, and in FIG. 5, Sheet 5 of 9, a H.323 protocol portion (item 33, FIG. 2), a CODEC (item 34, FIG. 2), and a call control portion (item 31, FIG. 2), that operate where a transmission format to be



used in accordance with each user information of a calling side is registered as a circuit, and a CODEC to be used in accordance with each user information of the calling side is registered as the CODEC, and if the user information of a calling side is accompanied by ON flag in the target parameter setting table, the reference table of the user information of the calling side and communication method is looked up, so that the transmission format to be used as the communication method is decided, and a request of setup is propagated to opposite site of the intended connection (item #311, FIG. 5) based on selection of CODEC and format (a transmitting device for transmitting a format type information which is determined by a determining section to an OVPN terminating device). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Morinaga since Morinaga teaches a system that involves storing user information and transmission parameters for use in efficient connection setup.

**In regards to Claim 56**, as discussed in the rejection of Claim 49, the '692 reference in view of Morinaga and French teaches an optical communication network and a plurality of converting sections which are disposed to correspond to plural different signal formats, for converting a first signal format and a second signal format alternately under conditions in which a first signal format which is used by a user's device which joins an OVPN and a second signal which is used in an OVPN are different from each other.

The '692 reference fails to teach a section for performing an alternate converting operation.

Morinaga teaches in column 5, line 60 through column 6, line 6, and in column 7, lines 45-59, and in FIG. 2, Sheet 2 of 9, a H.323 protocol portion (item 33, FIG. 2), a CODEC (item 34, FIG. 2), and a call control portion (item 31, FIG. 2), that operate where a transmission format to be used in accordance with each user information of a calling side is registered as a circuit, and a CODEC to be used in accordance with each user information of the calling side is registered as the CODEC, and if the user information of a calling side is accompanied by ON flag in the target parameter setting table, the reference table of the user information of the calling side and communication method is looked up, so that the transmission format to be used as the communication method is decided (a section for performing an alternate converting operation). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Morinaga since Morinaga teaches a system that involves storing user information and transmission parameters, allowing the system of the '692 reference to be able to adjust routing parameters that best serve a user's preferences or QoS requirements.

**Claim 31** is rejected under 35 U.S.C. 103(a) as being unpatentable over the '692 reference in view of Morinaga, French, and further in view of Tosey et al. (Patent No.: US 6,392,990 B1), hereafter referred to as Tosey.

**In regards to Claim 31**, as discussed in the rejection of Claim 30, the '692 reference in view of Morinaga and French teaches a user's device and an OVPN.

The '692 reference fails to teach a separating section for separating a user's device and a network, and a returning section for returning a test beam which is transmitted from a network.

Tosey teaches in column 7, lines 14-17 and 29-31, and in FIG. 2, Sheet 2 of 11, a network computing device (item 21, FIG. 2) that is part of a network of other network devices, and this network is separated from a WAN of users by a router (item 24, FIG. 2), and where the network computing device (item 21, FIG. 2) executes a link test to a peer network device, such as the router (item 24, FIG. 2), and determines if a peer network device has returned a response (a separating section for separating a user's device and a network, and a returning section for returning a test beam which is transmitted from a network). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Tosey since Tosey provides a method of testing connections of a network device to other network devices, including devices that connect it to another network and its users, and where the device being tested can respond to confirm connectivity, including connectivity to a network of users, allowing the system of the '692 reference to detect network failures and respond by developing paths to avoid them and reestablish connectivity.

**Claim 51** is rejected under 35 U.S.C. 103(a) as being unpatentable over the '692 reference in view of Morinaga, French, and further in view of Newell.

**In regards to Claim 51**, as discussed in the rejection of Claim 50, the '692 reference in view of Morinaga and French teaches a receiving and retrieving section, an alternate converting section, a first signal format type information which is employed by a user's device according to a control channel after a final connection confirmation is transmitted.

The '692 reference fails to teach retrieving whether or not there is a converting section for performing an operation, and a retrieving result indicating there is a section for performing an operation, a registering section for registering an IP address and a VPNID which are allocated to a user's device

Newell teaches in column 4, lines 11-27, devices exchange information concerning which protocol feature teaches does or does not support (retrieving whether or not there is a converting section for performing an operation, and a retrieving result indicating there is a section for performing an operation). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Newell since Newell provides a method in which devices in a network can inform other devices of network capabilities, allowing devices to make appropriate decision when routing requests, allowing the system of the '692 reference to performing routing based on the capabilities of other devices.

French teaches in paragraphs [0227] and [0275], assigned VPN IDs are stored as updated information within network objects, and a VPN creator ensures unique VPN

IDs are created such that duplicate addresses can exist within a VPN that has an assigned VPN ID, and a server generates an IP address on behalf of its client (a registering section for registering an IP address and a VPNID which are allocated to a user's device). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of French since French provides a system of maintaining and updating VPN IDs for IP addresses within virtual private networks, allowing the optical network of the '692 reference to provide optical VPN services to customers and provide the privacy, robustness, and cost effectiveness of virtual private networks.

**Claim 55** is rejected under 35 U.S.C. 103(a) as being unpatentable over the '692 reference in view of Morinaga, French, and further in view of Tosey.

**In regards to Claim 55**, as discussed in the rejection of Claim 53, the '692 reference in view of Morinaga and French teaches a base point device.

The '692 reference fails to teach a separating section for separating a user's device and a network, and a returning section for returning a test beam which is transmitted from a network.

Tosey teaches in column 7, lines 14-17 and 29-31, and in FIG. 2, Sheet 2 of 11, a network computing device (item 21, FIG. 2) that is part of a network of other network devices, and this network is separated from a WAN of users by a router (item 24, FIG. 2), and where the network computing device (item 21, FIG. 2) executes a link test to a peer network device, such as the router (item 24, FIG. 2), and determines if a peer

network device has returned a response (a separating section for separating a user's device and a network, and a returning section for returning a test beam which is transmitted from a network). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Tosey since Tosey provides a method of testing connections of a network device to other network devices, including devices that connect it to another network and its users, and where the device being tested can respond to confirm connectivity, including connectivity to a network of users, allowing the system of the '692 reference to detect network failures and respond by developing paths to avoid them and reestablish connectivity.

**Claims 58, 59, 64-66 and 69** are rejected under 35 U.S.C. 103(a) as being unpatentable over the '692 reference in view of Miyabe (Patent No.: US 7,024,113 B2) (hereafter referred to as Miyabe) and Oguchi.

**In regards to Claims 58, 59 and 66**, the '692 reference teaches in paragraph [0005], page 2, lines 40-43, 48-49 and 52-55, an optical transport network is intended to be a multi-service network that supports a wide variety of layers including SDH STM-N, SONET, ATM, IP, as well as other formats, to provide a universal transport medium for high bandwidth services, where client signals are mapped into the payload area of a frame structure called an optical transport unit (OUT), and where the payload to be carried from the client, i.e. the client signal, which may be ATM, SDH, STM-N, or IP, is mapped into an optical payload unit (OPU), and, in paragraph [0019], page 5, lines 50-

55, and in Fig. 1, page 18, a node N1 (Fig. 1), a node SNA (Fig. 1), a node SNB (Fig. 1), and a node N1 (Fig. 1) at the edges a conventional SDH network (optical network, and a plurality of converting sections, which are disposed so as to correspond to plural different first signal formats, for converting a first signal format and a second signal format alternatively under conditions in which the first signal format is used by a user's device and a second signal format which is used in the network are different from each other, a transmitting section for transmitting a first signal format which is transmitted from a user's device to an optical network by encapsulating a first signal format by a second signal format, and a transmitting section for transmitting an encapsulated signal which is encapsulated by a second signal format which is transmitted from an optical network to a user's device by de-encapsulating to a first signal format, and a terminating device for containing the user's device, and a transmitting section for transmitting a plurality of optical wavelength signals to an optical network).

The '692 reference fails to teach a multiplying and transmitting section for multiplying and transmitting a plurality of optical wavelength signals which are used in a user's device to an optical network, a separating and transmitting section for separating and transmitting multiplied optical wavelength signals which arrive from an optical network, and separating and transmitting a multiplied optical wavelength signals which arrive from a base point device so as to transmit to a predetermined course according to information which is notified from a notifying section, a notifying section for notifying an optical network of information for a wavelength which are transmitted under a multiplied condition so as to be used in a plurality of devices, and VPN.

Miyabe teaches in column 19, lines 44-52, and in column 12, line 63 through column 13, line 8, and in FIG. 19, Sheet 19 of 28, and in FIG. 24, Sheet 23 of 28, a wavelength multiplexer (item 9, FIG. 19) on an output side of an optical switch (a multiplying and transmitting section for multiplying and transmitting a plurality of optical wavelength signals which are used in a user's device to an optical network).

Miyabe also teaches in column 19, lines 44-52, and in column 12, line 63 through column 13, line 8, and in FIG. 19, Sheet 19 of 28, and in FIG. 24, Sheet 23 of 28, a wavelength demultiplexer (item 7, FIG. 19) on an input side of an optical switch which can receive signals from intermediate network devices (a separating and transmitting section for separating and transmitting multiplied optical wavelength signals which arrive from an optical network, and separating and transmitting a multiplied optical wavelength signals which arrive from a base point device so as to transmit to a predetermined course according to information which is notified from a notifying section).

Miyabe also teaches in column 19, lines 44-52, and in column 12, line 63 through column 13, line 8, and in FIG. 19, Sheet 19 of 28, and in FIG. 24, Sheet 23 of 28, an OXC5 (OPTICAL XC5, FIG. 24) transmits to OXC4 (OPTICAL XC4, FIG. 24), a wavelength notification message indicating a wavelength has been reserved for a new route, where the wavelength notification message includes a path identifier and a wavelength value for notification, and upon receipt of this message, OXC4 stores the wavelength value into a table entry corresponding to a path identifier of the new route in a wavelength management table (item 60, FIG. 19), where the entire content of the wavelength management table become to have effective values and the contents are



reflected to an optical switch (a notifying section for notifying an optical network of information for a wavelength which are transmitted under a multiplied condition so as to be used in a plurality of devices). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Miyabe since Miyabe provides a system that details the reception, transmission, and processing of wavelength signals in an optical network and how to update routing information to devices on such a network, and can be incorporated the system of the '692 reference to provide prompt management table updates utilizing wavelength division components.

Oguchi teaches in paragraph [0065], [0067], [0083], [0085], and [0143], virtual routers having the same VPN-ID exchange routing information though a level-2 tunnel established between edge routers, which can involves a host having an IP address, and then generate routing tables for that VPN-ID (VPN). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Oguchi since Oguchi provides a method of establishing a virtual network and distributing the necessary information to establish and maintain such a virtual network, allowing the optical network of the '692 reference to provide optical VPN services to customers and provide the privacy, robustness, and cost effectiveness of virtual private networks.

**In regards to Claims 64 and 65**, the '692 reference teaches in paragraph [0005], page 2, lines 40-43, 48-49 and 52-55, an optical transport network is intended to

be a multi-service network that supports a wide variety of layers including SDH STM-N, SONET, ATM, IP, as well as other formats, to provide a universal transport medium for high bandwidth services, where client signals are mapped into the payload area of a frame structure called an optical transport unit (OUT), and where the payload to be carried from the client, i.e. the client signal, which may be ATM, SDH, STM-N, or IP, is mapped into an optical payload unit (OPU), and, in paragraph [0019], page 5, lines 50-55, and in Fig. 1, page 18, a node N1 (Fig. 1), a node SNA (Fig. 1), a node SNB (Fig. 1), and a node N1 (Fig. 1) at the edges a conventional SDH network (optical network, and a plurality of converting sections, which are disposed so as to correspond to plural different first signal formats, for converting a first signal format and a second signal format alternatively under conditions in which the first signal format is used by a user's device and a second signal format which is used in the network are different from each other, a transmitting section for transmitting a first signal format which is transmitted from a user's device to an optical network by encapsulating a first signal format by a second signal format, and a terminating device for containing the user's device).

The '692 reference fails to teach converting a series of serial signals into a plurality of parallel signals and covering a plurality of parallel signals into a series of serial signals, and VPN.

Miyabe teaches in column 19, lines 44-52, and in column 12, line 63 through column 13, line 8, and in FIG. 19, Sheet 19 of 28, and in FIG. 24, Sheet 23 of 28, a wavelength multiplexer (item 9, FIG. 19) on an output side of an optical switch, and a wavelength demultiplexer (item 7, FIG. 19) on an input side of an optical switch which

can receive signals from intermediate network devices (converting a series of serial signals into a plurality of parallel signals and covering a plurality of parallel signals into a series of serial signals). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Miyabe since Miyabe provides a system that details the reception, transmission, and processing of wavelength signals in an optical network and how to update routing information to devices on such a network, and can be incorporated the system of the '692 reference to provide prompt management table updates utilizing wavelength division components.

Oguchi teaches in paragraph [0065], [0067], [0083], [0085], and [0143], virtual routers having the same VPN-ID exchange routing information though a level-2 tunnel established between edge routers, which can involves a host having an IP address, and then generate routing tables for that VPN-ID (VPN). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Oguchi since Oguchi provides a method of establishing a virtual network and distributing the necessary information to establish and maintain such a virtual network, allowing the optical network of the '692 reference to provide optical VPN services to customers and provide the privacy, robustness, and cost effectiveness of virtual private networks.

**In regards to Claim 69**, the '692 reference teaches in paragraph [0005], page 2, lines 40-43, 48-49 and 52-55, an optical transport network is intended to be a multi-

service network that supports a wide variety of layers including SDH STM-N, SONET, ATM, IP, as well as other formats, to provide a universal transport medium for high bandwidth services, where client signals are mapped into the payload area of a frame structure called an optical transport unit (OUT), and where the payload to be carried from the client, i.e. the client signal, which may be ATM, SDH, STM-N, or IP, is mapped into an optical payload unit (OPU), and, in paragraph [0019], page 5, lines 50-55, and in Fig. 1, page 18, a node N1 (Fig. 1), a node SNA (Fig. 1), a node SNB (Fig. 1), and a node N1 (Fig. 1) at the edges a conventional SDH network (optical network, and a plurality of converting sections, which are disposed so as to correspond to plural different first signal formats, for converting a first signal format and a second signal format alternatively under conditions in which the first signal format is used by a user's device and a second signal format which is used in the network are different from each other, a transmitting section for transmitting a first signal format which is transmitted from a user's device to an optical network by encapsulating a first signal format by a second signal format, and a transmitting section for transmitting an encapsulated signal which is encapsulated by a second signal format which is transmitted from an optical network to a user's device by de-encapsulating to a first signal format, and a terminating device for containing the user's device, and a transmitting section for transmitting a plurality of optical wavelength signals to an optical network).

The '692 reference fails to teach a multiplying and transmitting section for multiplying and transmitting a plurality of optical wavelength signals which are used in a user's device to an optical network, a separating and transmitting section for separating

and transmitting multiplied optical wavelength signals which arrive from an optical network, and separating and transmitting a multiplied optical wavelength signals which arrive from a base point device so as to transmit to a predetermined course according to information which is notified from a notifying section, a notifying section for notifying an optical network of information for a wavelength which are transmitted under a multiplied condition so as to be used in a plurality of devices, and VPN.

Miyabe teaches in column 19, lines 44-52, and in column 12, line 63 through column 13, line 8, and in FIG. 19, Sheet 19 of 28, and in FIG. 24, Sheet 23 of 28, a wavelength multiplexer (item 9, FIG. 19) on an output side of an optical switch (a multiplying and transmitting section for multiplying and transmitting a plurality of optical wavelength signals which are used in a user's device to an optical network).

Miyabe also teaches in column 19, lines 44-52, and in column 12, line 63 through column 13, line 8, and in FIG. 19, Sheet 19 of 28, and in FIG. 24, Sheet 23 of 28, a wavelength demultiplexer (item 7, FIG. 19) on an input side of an optical switch which can receive signals from intermediate network devices (a separating and transmitting section for separating and transmitting multiplied optical wavelength signals which arrive from an optical network, and separating and transmitting a multiplied optical wavelength signals which arrive from a base point device so as to transmit to a predetermined course according to information which is notified from a notifying section).

Miyabe also teaches in column 19, lines 44-52, and in column 12, line 63 through column 13, line 8, and in FIG. 19, Sheet 19 of 28, and in FIG. 24, Sheet 23 of 28, a an OXC5 (OPTICAL XC5, FIG. 24) transmits to OXC4 (OPTICAL XC4, FIG. 24), a

wavelength notification message indicating a wavelength has been reserved for a new route, where the wavelength notification message includes a path identifier and a wavelength value for notification, and upon receipt of this message, OXC4 stores the wavelength value into a table entry corresponding to a path identifier of the new route in a wavelength management table (item 60, FIG. 19), where the entire content of the wavelength management table become to have effective values and the contents are reflected to an optical switch (a notifying section for notifying an optical network of information for a wavelength which are transmitted under a multiplied condition so as to be used in a plurality of devices). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Miyabe since Miyabe provides a system that details the reception, transmission, and processing of wavelength signals in an optical network and how to update routing information to devices on such a network, and can be incorporated the system of the '692 reference to provide prompt management table updates utilizing wavelength division components.

Oguchi teaches in paragraph [0065], [0067], [0083], [0085], and [0143], virtual routers having the same VPN-ID exchange routing information though a level-2 tunnel established between edge routers, which can involves a host having an IP address, and then generate routing tables for that VPN-ID (VPN). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Oguchi since Oguchi provides a method of establishing a virtual network and distributing the necessary information to establish and maintain such

a virtual network, allowing the optical network of the '692 reference to provide optical VPN services to customers and provide the privacy, robustness, and cost effectiveness of virtual private networks.

**Claims 60-63** are rejected under 35 U.S.C. 103(a) as being unpatentable over the '692 reference in view of Miyabe, Miller et al. (Patent No.: US 6,212,568 B1) (hereafter referred to as Miller), and Oguchi.

**In regards to Claim 60**, the '692 reference teaches in paragraph [0005], page 2, lines 40-43, 48-49 and 52-55, an optical transport network is intended to be a multi-service network that supports a wide variety of layers including SDH STM-N, SONET, ATM, IP, as well as other formats, to provide a universal transport medium for high bandwidth services, where client signals are mapped into the payload area of a frame structure called an optical transport unit (OUT), and where the payload to be carried from the client, i.e. the client signal, which may be ATM, SDH, STM-N, or IP, is mapped into an optical payload unit (OPU), and, in paragraph [0019], page 5, lines 50-55, and in Fig. 1, page 18, a node N1 (Fig. 1), a node SNA (Fig. 1), a node SNB (Fig. 1), and a node N1 (Fig. 1) at the edges a conventional SDH network (optical network, and a plurality of converting sections, which are disposed so as to correspond to plural different first signal formats, for converting a first signal format and a second signal format alternatively under conditions in which the first signal format is used by a user's device and a second signal format which is used in the network are different from each other, a transmitting section for transmitting a first signal format which is transmitted from a

user's device to an optical network by encapsulating a first signal format by a second signal format, and a transmitting section for transmitting an encapsulated signal which is encapsulated by a second signal format which is transmitted from an optical network to a user's device by de-encapsulating to a first signal format, and a terminating device for containing the user's device, and a transmitting section for transmitting a plurality of optical wavelength signals to an optical network).

The '692 reference fails to teach a converting and transmitting section for converting a serial signal which is transmitted from a user's device into a plurality of parallel signals so as to transmit to a network, a converting and transmitting section for converting a plurality of parallel signals which arrive from a network to a serial signal so as to transmit to a user's device a notifying section for notifying that information for a topology of parallel signals and information that the serial signals are converted to parallel signals, and VPN.

Miyabe teaches in column 19, lines 44-52, and in column 12, line 63 through column 13, line 8, and in FIG. 19, Sheet 19 of 28, and in FIG. 24, Sheet 23 of 28, a wavelength demultiplexer (item 7, FIG. 19) on an input side of an optical switch which can receive signals from intermediate network devices (a converting and transmitting section for converting a serial signal which is transmitted from a user's device into a plurality of parallel signals so as to transmit to a network).

Miyabe also teaches in column 19, lines 44-52, and in column 12, line 63 through column 13, line 8, and in FIG. 19, Sheet 19 of 28, and in FIG. 24, Sheet 23 of 28, a wavelength multiplexer (item 9, FIG. 19) on an output side of an optical switch (a



converting and transmitting section for converting a plurality of parallel signals which arrive from a network to a serial signal so as to transmit to a user's device). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Miyabe since Miyabe provides a system that details the reception, transmission, and processing of wavelength signals in an optical network and how to update routing information to devices on such a network, and can be incorporated the system of the '692 reference to provide prompt management table updates utilizing wavelength division components.

Miller teaches in column 11, lines 4-11, a frame includes a frames-follow flag which indicates that multiple frames together comprise a "super frame" (a notifying section for notifying that information for a topology of parallel signals and information that the serial signals are converted to parallel signals). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Miller since Miller provides a method of conveying how information has been arranged, allowing quicker processing of data units since more detailed information is provided to devices that receive the encapsulated data unit in the system of the '692 reference.

Oguchi teaches in paragraph [0065], [0067], [0083], [0085], and [0143], virtual routers having the same VPN-ID exchange routing information though a level-2 tunnel established between edge routers, which can involves a host having an IP address, and then generate routing tables for that VPN-ID (VPN). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692

reference with the invention of Oguchi since Oguchi provides a method of establishing a virtual network and distributing the necessary information to establish and maintain such a virtual network, allowing the optical network of the '692 reference to provide optical VPN services to customers and provide the privacy, robustness, and cost effectiveness of virtual private networks.

**In regards to Claim 61**, as discussed in the rejection of Claim 60, the '692 reference in view of Miyabe, Miller, and Oguchi teaches an optical network, and a plurality of converting sections, which are disposed so as to correspond to plural different first signal formats, for converting a first signal format and a second signal format alternatively under conditions in which the first signal format is used by a user's device and a second signal format which is used in the network are different from each other, and a terminating device for containing the user's device and information which is notified from a notifying section.

The '692 reference fails to teach an inputting section for inputting parallel signals which are divided from a series of serial signals.

Miyabe further teaches in column 19, lines 44-52, and in column 12, line 63 through column 13, line 8, and in FIG. 19, Sheet 19 of 28, and in FIG. 24, Sheet 23 of 28, a wavelength multiplexer (item 9, FIG. 19) on an output side of an optical switch (an inputting section for inputting parallel signals which are divided from a series of serial signals). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Miyabe

since Miyabe provides a system that details the reception, transmission, and processing of wavelength signals in an optical network and how to update routing information to devices on such a network, and can be incorporated the system of the '692 reference to provide prompt management table updates utilizing wavelength division components.

**In regards to Claims 62 and 63**, the '692 reference teaches in paragraph [0005], page 2, lines 40-43, 48-49 and 52-55, an optical transport network is intended to be a multi-service network that supports a wide variety of layers including SDH STM-N, SONET, ATM, IP, as well as other formats, to provide a universal transport medium for high bandwidth services, where client signals are mapped into the payload area of a frame structure called an optical transport unit (OUT), and where the payload to be carried fro the client, i.e. the client signal, which may be ATM, SDH, STM-N, or IP, is mapped into an optical payload unit (OPU), and, in paragraph [0019], page 5, lines 50-55, and in Fig. 1, page 18, a node N1 (Fig. 1), a node SNA (Fig. 1), a node SNB (Fig. 1), and a node N1 (Fig. 1) at the edges a conventional SDH network (optical network, and a plurality of converting sections, which are disposed so as to correspond to plural different first signal formats, for converting a first signal format and a second signal format alternatively under conditions in which the first signal format is used by a user's device and a second signal format which is used in the network are different from each other, and a terminating device for containing the user's device,).

The '692 reference fails to teach a multiplying and transmitting section for multiplying a parallel signal which is converted from a serial signal to transmit to a

network, a separating and transmitting section for separating multiplied wavelength signals which arrive from a network into parallel signals and converting parallel signals into serial signals so as to transmit to a device, information that signals are transmitted under wavelength-multiplied condition, a notifying section for notifying that information for a topology of parallel signals, and VPN.

Miyabe teaches in column 19, lines 44-52, and in column 12, line 63 through column 13, line 8, and in FIG. 19, Sheet 19 of 28, and in FIG. 24, Sheet 23 of 28, a wavelength multiplexer (item 9, FIG. 19) on an output side of an optical switch (a multiplying and transmitting section for multiplying a parallel signal which is converted from a serial signal to transmit to a network).

Miyabe also teaches in column 19, lines 44-52, and in column 12, line 63 through column 13, line 8, and in FIG. 19, Sheet 19 of 28, and in FIG. 24, Sheet 23 of 28, a wavelength demultiplexer (item 7, FIG. 19) on an input side of an optical switch which can receive signals from intermediate network devices (a separating and transmitting section for separating multiplied wavelength signals which arrive from a network into parallel signals and converting parallel signals into serial signals so as to transmit to a device).

Miyabe also teaches in column 19, lines 44-52, and in column 12, line 63 through column 13, line 8, and in FIG. 19, Sheet 19 of 28, and in FIG. 24, Sheet 23 of 28, a an OXC5 (OPTICAL XC5, FIG. 24) transmits to OXC4 (OPTICAL XC4, FIG. 24), a wavelength notification message indicating a wavelength has been reserved for a new route, where the wavelength notification message includes a path identifier and a

wavelength value for notification, and upon receipt of this message, OXC4 stores the wavelength value into a table entry corresponding to a path identifier of the new route in a wavelength management table (item 60, FIG. 19), where the entire content of the wavelength management table become to have effective values and the contents are reflected to an optical switch (information that signals are transmitted under wavelength-multiplied condition). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Miyabe since Miyabe provides a system that details the reception, transmission, and processing of wavelength signals in an optical network and how to update routing information to devices on such a network, and can be incorporated the system of the '692 reference to provide prompt management table updates utilizing wavelength division components.

Miller teaches in column 11, lines 4-11, a frame includes a frames-follow flag which indicates that multiple frames together comprise a "super frame" (a notifying section for notifying that information for a topology of parallel signals). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Miller since Miller provides a method of conveying how information has been arranged, allowing quicker processing of data units since more detailed information is provided to devices that receive the encapsulated data unit in the system of the '692 reference.

Oguchi teaches in paragraph [0065], [0067], [0083], [0085], and [0143], virtual routers having the same VPN-ID exchange routing information though a level-2 tunnel

established between edge routers, which can involve a host having an IP address, and then generate routing tables for that VPN-ID (VPN). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Oguchi since Oguchi provides a method of establishing a virtual network and distributing the necessary information to establish and maintain such a virtual network, allowing the optical network of the '692 reference to provide optical VPN services to customers and provide the privacy, robustness, and cost effectiveness of virtual private networks.

**Claim 67** is rejected under 35 U.S.C. 103(a) as being unpatentable over the '692 reference in view of Miyabe, Oguchi, and further in view of Tosey et al. (Patent No.: US 6,392,990 B1), hereafter referred to as Tosey.

**In regards to Claim 67**, as discussed in the rejection of Claim 58, the '692 reference in view of Miyabe and Oguchi teaches a user's device and an OVPN.

The '692 reference fails to teach a separating section for separating a user's device and a network, and a returning section for returning a test beam which is transmitted from a network.

Tosey teaches in column 7, lines 14-17 and 29-31, and in FIG. 2, Sheet 2 of 11, a network computing device (item 21, FIG. 2) that is part of a network of other network devices, and this network is separated from a WAN of users by a router (item 24, FIG. 2), and where the network computing device (item 21, FIG. 2) executes a link test to a peer network device, such as the router (item 24, FIG. 2), and determines if a peer

network device has returned a response (a separating section for separating a user's device and a network, and a returning section for returning a test beam which is transmitted from a network). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Tosey since Tosey provides a method of testing connections of a network device to other network devices, including devices that connect it to another network and its users, and where the device being tested can respond to confirm connectivity, including connectivity to a network of users, allowing the system of the '692 reference to detect network failures and respond by developing paths to avoid them and reestablish connectivity.

**Claim 68** is rejected under 35 U.S.C. 103(a) as being unpatentable over the '692 reference in view of Miyabe, Oguchi, and further in view of Morinaga.

**In regards to Claim 68**, as discussed in the rejection of Claim 59, the '692 reference in view of Oguchi teaches an OVPN terminating device and a plurality of converting sections which are disposed to correspond to plural different signal formats, for converting a first signal format and a second signal format alternately under conditions in which a first signal format which is used by a user's device which joins an OVPN and a second signal which is used in an OVPN are different from each other.

The '692 reference fails to teach a section for performing an alternate converting operation.

Morinaga teaches in column 5, line 60 through column 6, line 6, and in column 7, lines 45-59, and in FIG. 2, Sheet 2 of 9, a H.323 protocol portion (item 33, FIG. 2), a CODEC (item 34, FIG. 2), and a call control portion (item 31, FIG. 2), that operate where a transmission format to be used in accordance with each user information of a calling side is registered as a circuit, and a CODEC to be used in accordance with each user information of the calling side is registered as the CODEC, and if the user information of a calling side is accompanied by ON flag in the target parameter setting table, the reference table of the user information of the calling side and communication method is looked up, so that the transmission format to be used as the communication method is decided (a section for performing an alternate converting operation). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Morinaga since Morinaga teaches a system that involves storing user information and transmission parameters, allowing the system of the '692 reference to be able to adjust routing parameters that best serve a user's preferences or QoS requirements.

**Claims 70-74** are rejected under 35 U.S.C. 103(a) as being unpatentable over the '692 reference in view of Oguchi and Tosey.

**In regards to Claims 70, 71 and 73**, the '692 reference teaches in paragraph [0005], page 2, lines 40-43, 48-49 and 52-55, an optical transport network is intended to be a multi-service network that supports a wide variety of layers including SDH STM-N, SONET, ATM, IP, as well as other formats, to provide a universal transport medium for



high bandwidth services, where client signals are mapped into the payload area of a frame structure called an optical transport unit (OUT), and where the payload to be carried from the client, i.e. the client signal, which may be ATM, SDH, STM-N, or IP, is mapped into an optical payload unit (OPU), and, in paragraph [0019], page 5, lines 50-55, and in Fig. 1, page 18, a node N1 (Fig. 1), a node SNA (Fig. 1), a node SNB (Fig. 1), and a node N1 (Fig. 1) at the edges of a conventional SDH network (optical network, and a plurality of converting sections, which are disposed so as to correspond to plural different first signal formats, for converting a first signal format and a second signal format alternatively under conditions in which the first signal format is used by a user's device and a second signal format which is used in the network are different from each other, a transmitting section for transmitting a first signal format which is transmitted from a user's device to an optical network by encapsulating a first signal format by a second signal format, and a terminating device for containing the user's device).

The '692 reference fails to teach a recording section for recording a group for a device which relates to a common VPNID, and VPN, a selecting section for detecting an occurrence of a failure in a control channel and a data channel, a requesting section requesting that other device in a same group should perform processes which is supposed to be performed by original device which has a failure in a control channel with reference to a recording section when detecting section detects an occurrence of a failure.

Oguchi teaches in paragraph [0065], [0067], [0083], [0085], and [0143], virtual routers having the same VPN-ID exchange routing information through a level-2 tunnel

established between edge routers, which can involves a host having an IP address, and then generate routing tables for that VPN-ID (a recording section for recording a group for a device witch relates to a common VPNID, and VPN). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Oguchi since Oguchi provides a method of establishing a virtual network and distributing the necessary information to establish and maintain such a virtual network, allowing the optical network of the '692 reference to provide optical VPN services to customers and provide the privacy, robustness, and cost effectiveness of virtual private networks.

Tosey teaches in column 8, lines 59-67, and in column 9, lines 12-32, and in FIG. 6B, Sheet 9 of 11, a failure occurs in the connection between a computing device (item 163, FIG. 6B) and a router A (item 172, FIG. 6B), which causes the computing device to switch communications though a new interface that connects to a WAN though router B (item 174, FIG. 6B), and a routing protocol, such as RIP or OSPF, is used to notify external network components that packets must be rerouted to the new network interface that is connected to the WAN though router B (item 174, FIG. 6B) (a selecting section for detecting an occurrence of a failure in a control channel and a data channel, a requesting section requesting that other device in a same group should perform processes which is supposed to be performed by original device which has a failure in a control channel with reference to a recoding section when detecting section detects an occurrence of a failure). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the

invention of Tosey since Tosey provides a method of testing connections of a network device to other network devices, including devices that connect it to another network and its users, and where the device being tested can respond to confirm connectivity, including connectivity to a network of users, allowing the system of the '692 reference to detect network failures and respond by developing paths to avoid them and reestablish connectivity.

**In regards to Claim 72**, as discussed in the rejection of Claim 58, the '692 reference in view of Oguchi and Tosey teaches a user's device and an OVPN.

The '692 reference fails to teach a separating section for separating a user's device and a network, and a returning section for returning a test beam which is transmitted from a network.

Tosey teaches in column 7, lines 14-17 and 29-31, and in FIG. 2, Sheet 2 of 11, a network computing device (item 21, FIG. 2) that is part of a network of other network devices, and this network is separated from a WAN of users by a router (item 24, FIG. 2), and where the network computing device (item 21, FIG. 2) executes a link test to a peer network device, such as the router (item 24, FIG. 2), and determines if a peer network device has returned a response (a separating section for separating a user's device and a network, and a returning section for returning a test beam which is transmitted from a network). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Tosey since Tosey provides a method of testing connections of a network

device to other network devices, including devices that connect it to another network and its users, and where the device being tested can respond to confirm connectivity, including connectivity to a network of users, allowing the system of the '692 reference to detect network failures and respond by developing paths to avoid them and reestablish connectivity.

**In regards to Claim 74**, the '692 reference teaches in paragraph [0005], page 2, lines 40-43, 48-49 and 52-55, an optical transport network is intended to be a multi-service network that supports a wide variety of layers including SDH STM-N, SONET, ATM, IP, as well as other formats, to provide a universal transport medium for high bandwidth services, where client signals are mapped into the payload area of a frame structure called an optical transport unit (OUT), and where the payload to be carried from the client, i.e. the client signal, which may be ATM, SDH, STM-N, or IP, is mapped into an optical payload unit (OPU), and, in paragraph [0019], page 5, lines 50-55, and in Fig. 1, page 18, a node N1 (Fig. 1), a node SNA (Fig. 1), a node SNB (Fig. 1), and a node N1 (Fig. 1) at the edges a conventional SDH network (optical network, and a plurality of converting sections, which are disposed so as to correspond to plural different first signal formats, for converting a first signal format and a second signal format alternatively under conditions in which the first signal format is used by a user's device and a second signal format which is used in the network are different from each other, a transmitting section for transmitting a first signal format which is transmitted from a

user's device to an optical network by encapsulating a first signal format by a second signal format, and a terminating device for containing the user's device).

The '692 reference fails to teach a recording section for recording a group for a device witch relates to a common VPNID, and VPN, a selecting section for detecting an occurrence of a failure in a control channel and a data channel, a requesting section requesting that other device in a same group should perform processes which is supposed to be performed by original device which has a failure in a control channel with reference to a recoding section when detecting section detects an occurrence of a failure.

Oguchi teaches in paragraph [0065], [0067], [0083], [0085], and [0143], virtual routers having the same VPN-ID exchange routing information though a level-2 tunnel established between edge routers, which can involves a host having an IP address, and then generate routing tables for that VPN-ID (a recording section for recording a group for a device witch relates to a common VPNID, and VPN). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Oguchi since Oguchi provides a method of establishing a virtual network and distributing the necessary information to establish and maintain such a virtual network, allowing the optical network of the '692 reference to provide optical VPN services to customers and provide the privacy, robustness, and cost effectiveness of virtual private networks.

Tosey teaches in column 8, lines 59-67, and in column 9, lines 12-32, and in FIG. 6B, Sheet 9 of 11, a failure occurs in the connection between a computing device (item

163, FIG. 6B) and a router A (item 172, FIG. 6B), which causes the computing device to switch communications through a new interface that connects to a WAN through router B (item 174, FIG. 6B), and a routing protocol, such as RIP or OSPF, is used to notify external network components that packets must be rerouted to the new network interface that is connected to the WAN through router B (item 174, FIG. 6B) (a selecting section for detecting an occurrence of a failure in a control channel and a data channel, a requesting section requesting that other device in a same group should perform processes which is supposed to be performed by original device which has a failure in a control channel with reference to a recoding section when detecting section detects an occurrence of a failure). It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the invention of the '692 reference with the invention of Tosey since Tosey provides a method of testing connections of a network device to other network devices, including devices that connect it to another network and its users, and where the device being tested can respond to confirm connectivity, including connectivity to a network of users, allowing the system of the '692 reference to detect network failures and respond by developing paths to avoid them and reestablish connectivity.

### ***Response to Arguments***

Applicant's arguments filed 08/25/2008 have been fully considered but they are not persuasive. Applicant submits that in Applicant's present invention, the first signal format is Gigabit Ethernet or ATM, and the second signal format is SDH, and Applicant

believes that Morinaga et al. could not be an applicable citation since Morinaga et al. discloses a different technology associated with a protocol for selecting media, e.g. CODEC, among a plurality of GWs from that of the present invention. Examiner respectfully disagrees this is sufficient for the withdrawal of the rejections of Applicant's claims. Although Morinaga discloses a different technology associated with a protocol for selecting media, and that the invention of Applicant involves a first signal format is Gigabit Ethernet or ATM and the second signal format is SDH, these limitations are not clearly claimed in Applicant's Claim 1. As a result, Claim 1 of Applicant does not contain limitations that clearly distinguish from the teachings of the combination of the '692 reference, Morinaga, and Oguchi.

Applicant also submits that "no data cells" disclosed in paragraph [0130] of Zboril et al. does not correspond to a vacancy of alternate converting operation of Claims 5 and 6 of the Application. Examiner respectfully disagrees this is sufficient for the withdrawal of the rejections of Applicant's claims. When no data cells are available on a data link 120 (Zboril, FIG. 3), this indicates that at least a Transmit Formatter (Zboril, FIG. 3, item 106) is not processing and transmitting data cells over a data link 120 and, as a result, is substantively the same as a "vacancy of a section for an operation" of Claims 5 and 6 of the Application.

Applicant also submits that, basically, the present invention relates to VPN achieved on a layer 1 on an optical network including OVPNs using WDM apparatuses, and the present invention has an effect in which VPNID or an IP address can be allocated per wavelength, i.e., user's bandwidth can be allocated based on wavelength,

and, more specifically, a wavelength can be correlated to signal format type (SDH, STM, etc.), and the wavelength can be correlated to users (user 1, user 2...) by using the VPNID or the IP address as a key, and Oguchi et al. and Zboril et al. cannot achieve this superior effect. Examiner respectfully disagrees this is sufficient for the withdrawal of the rejections of Applicant's claims. Claims 5 and 6 of Applicant do not clearly contain these limitations and Claims 5 and 6 do not contain limitations that clearly distinguish from the teachings of the combination of the '692 reference, Morinaga, Oguchi, and Zboril.

### ***Conclusion***

3. Applicant's amendment necessitated the new ground(s) of rejection presented in this Office action. Accordingly, **THIS ACTION IS MADE FINAL**. See MPEP § 706.07(a). Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the date of this final action.



Any inquiry concerning this communication or earlier communications from the examiner should be directed to JOSHUA SMITH whose telephone number is (571)270-1826. The examiner can normally be reached on Monday-Thursday 9:30am-7pm, Alternating Fridays 9:30am-6pm, EST.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Hassan Kizou can be reached on 571-272-3088. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

Joshua Smith  
Patent Examiner  
08 December 2008

/Hassan Kizou/  
Supervisory Patent Examiner, Art Unit 2419